
django-cas-server Documentation

Release 2.0.0

Valentin Samir

Sep 13, 2023

Contents

1	CAS Server	3
1.1	Features	4
1.2	Dependencies	4
1.3	Installation	5
1.4	Quick start	6
1.5	Settings	7
1.5.1	Template settings	7
1.5.2	Authentication settings	8
1.5.3	Federation settings	9
1.5.4	New version warnings settings	9
1.5.5	Tickets validity settings	9
1.5.6	Tickets miscellaneous settings	9
1.5.7	Mysql backend settings	10
1.5.8	Sql backend settings	10
1.5.9	Ldap backend settings	11
1.5.10	Test backend settings	11
1.6	Authentication backend	12
1.7	Logs	12
1.8	Service Patterns	13
1.9	Federation mode	14
2	cas_server package	17
2.1	Subpackages	17
2.1.1	cas_server.templatetags package	17
2.2	Submodules	18
2.2.1	cas_server.admin module	18
2.2.2	cas_server.apps module	20
2.2.3	cas_server.auth module	21
2.2.4	cas_server.cas module	24
2.2.5	cas_server.default_settings module	26
2.2.6	cas_server.federate module	30
2.2.7	cas_server.forms module	31
2.2.8	cas_server.models module	33
2.2.9	cas_server.urls module	48
2.2.10	cas_server.utils module	48
2.2.11	cas_server.views module	52

2.3	Module contents	60
3	Change Log	61
3.1	Unreleased	62
3.1.1	Added	62
3.2	v2.0.0 - 2022-10-17	62
3.2.1	Added	62
3.2.2	Changed	62
3.2.3	Fixes	63
3.2.4	Removed	63
3.3	v1.3.1 - 2021-07-03	63
3.3.1	Fixes	63
3.4	v1.3.0 - 2021-06-19	63
3.4.1	Added	63
3.4.2	Fixes	63
3.4.3	Removed	63
3.5	v1.2.0 - 2020-07-05	64
3.5.1	Added	64
3.5.2	Fixes	64
3.5.3	Changed	64
3.5.4	Removed	64
3.6	v1.1.0 - 2019-03-02	64
3.6.1	Added	64
3.6.2	Fixes	64
3.7	v1.0.0 - 2019-01-12	64
3.7.1	Added	64
3.7.2	Fixes	65
3.7.3	Deprecated	65
3.7.4	Other	65
3.8	v0.9.0 - 2017-11-17	65
3.8.1	Added	65
3.8.2	Fixed	65
3.9	v0.8.0 - 2017-03-08	66
3.9.1	Added	66
3.9.2	Fixed	66
3.9.3	Changed	66
3.10	v0.7.4 - 2016-09-07	66
3.10.1	Fixed	66
3.11	v0.7.3 - 2016-09-07	66
3.11.1	Added	66
3.11.2	Fixed	66
3.12	v0.7.2 - 2016-08-31	67
3.12.1	Added	67
3.12.2	Fixed	67
3.13	v0.7.1 - 2016-08-24	67
3.13.1	Added	67
3.14	v0.7.0 - 2016-08-24	67
3.14.1	Added	67
3.14.2	Changed	67
3.14.3	Fixed	67
3.15	v0.6.4 - 2016-08-14	68
3.15.1	Added	68
3.16	v0.6.3 - 2016-08-14	68
3.16.1	Added	68

	3.16.2	Changed	68
	3.16.3	Fixed	68
	3.16.4	Cleaned	68
3.17	v0.6.2 - 2016-08-02		68
	3.17.1	Added	69
	3.17.2	Changed	69
	3.17.3	Deprecated	69
	3.17.4	Fixed	69
	3.17.5	Cleaned	69
3.18	v0.6.1 - 2016-07-27		69
	3.18.1	Added	70
	3.18.2	Changed	70
	3.18.3	Fixed	70
	3.18.4	Cleaned	70
3.19	v0.6.0 - 2016-07-06		70
	3.19.1	Added	70
	3.19.2	Fixed	70
3.20	v0.5.0 - 2016-07-01		71
	3.20.1	Added	71
	3.20.2	Changed	71
	3.20.3	Fixed	71
	3.20.4	Cleaned	71
3.21	v0.4.4 - 2016-04-30		72
	3.21.1	Added	72
	3.21.2	Fixed	72
	3.21.3	Changed	72
3.22	v0.4.3 - 2016-03-18		72
	3.22.1	Fixed	72
3.23	v0.4.2 - 2016-03-18		73
	3.23.1	Added	73
	3.23.2	Fixed	73
3.24	v0.4.1 - 2015-12-23		73
	3.24.1	Added	73
	3.24.2	Changed	73
	3.24.3	Fixed	73
3.25	v0.4.0 - 2015-12-15		73
	3.25.1	Added	74
3.26	v0.3.5 - 2015-12-12		74
	3.26.1	Added	74
	3.26.2	Changed	74
	3.26.3	Fixed	74
3.27	v0.3.4 - 2015-12-12		74
	3.27.1	Added	74
3.28	v0.3.3 - 2015-12-12		74
	3.28.1	Added	74
3.29	v0.3.2 - 2015-12-12 [YANKED]		75
	3.29.1	Added	75
3.30	v0.3.1 - 2015-12-12		75
	3.30.1	Added	75
3.31	v0.3.0 - 2015-12-12		75
	3.31.1	Added	75
3.32	v0.2.1 - 2015-12-12		75
	3.32.1	Fixed	75
3.33	v0.2.0 - 2015-12-12 [YANKED]		75

3.34 v0.1.0 - 2015-05-22 [YANKED]	76
4 Indices and tables	77
Python Module Index	79
Index	81

Contents:

CHAPTER 1

CAS Server

CAS Server is a Django application implementing the [CAS Protocol 3.0 Specification](#).

By default, the authentication process uses django internal users but you can easily use any source (see the [Authentication backend](#) section and auth classes in the `auth.py` file)

Table of Contents

- *CAS Server*
 - *Features*
 - *Dependencies*
 - *Installation*
 - *Quick start*
 - *Settings*
 - * *Template settings*
 - * *Authentication settings*
 - * *Federation settings*
 - * *New version warnings settings*
 - * *Tickets validity settings*
 - * *Tickets miscellaneous settings*
 - * *Mysql backend settings*
 - * *Sql backend settings*
 - * *Ldap backend settings*

* *Test backend settings*

- *Authentication backend*
- *Logs*
- *Service Patterns*
- *Federation mode*

1.1 Features

- Support CAS version 1.0, 2.0, 3.0
- Support Single Sign Out
- Configuration of services via the Django Admin application
- Fine control on which user's attributes are passed to which service
- Possibility to rename/rewrite attributes per service
- Possibility to require some attribute values per service
- Federated mode between multiple CAS
- Supports Django 1.11, 2.2, 3.2, 4.2
- Supports Python 3.6+

1.2 Dependencies

django-cas-server depends on the following python packages:

- Django $\geq 1.11 < 4.3$
- requests ≥ 2.4
- requests_futures $\geq 0.9.5$
- lxml ≥ 3.4
- six ≥ 1.8

Minimal version of package dependencies are just indicative and means that django-cas-server has been tested with it. Previous versions of dependencies may or may not work.

Additionally, depending on the *Authentication backend* you plan to use, you may need the following python packages:

- ldap3
- psycpg2
- mysql-python

Here is a table with the name of python packages and the corresponding packages providing them on debian like systems and centos like systems. You should try as much as possible to use system packages as they are automatically updated when you update your system. You can then install Not Available (N/A) packages on your system using pip3 inside a virtualenv as described in the *Installation* section. For use with python2, just replace python3(6) in the table by python.

python package	debian like systems	centos like systems
Django	python3-django	python36-django
requests	python3-requests	python36-requests
requests_futures	python3-requests-futures	N/A
lxml	python3-lxml	python36-lxml
six	python3-six	python36-six
ldap3	python3-ldap3	python36-ldap3
psycpg2	python3-psycpg2	python36-psycpg2
mysql-python	python3-mysqldb	python36-mysql

1.3 Installation

The recommended installation mode is to use a virtualenv with `--system-site-packages`

1. Make sure that python virtualenv is installed
2. Install python packages available via the system package manager:

On debian like systems:

```
$ sudo apt-get install python3-django python3-requests python3-six python3-lxml
↪python3-requests-futures
```

On debian jessie, you can use the version of python-django available in the [backports](#).

On centos like systems with epel enabled:

```
$ sudo yum install python36-django python36-requests python36-six python36-lxml
```

3. Create a virtualenv:

```
$ virtualenv -p python3 --system-site-packages cas_venv
```

4. And activate it:

```
$ cd cas_venv/; . bin/activate
```

5. Create a django project:

```
$ django-admin startproject cas_project
$ cd cas_project
```

6. Install *django-cas-server*. To use the last published release, run:

```
$ pip install django-cas-server
```

Alternatively if you want to use the version of the git repository, you can clone it:

```
$ git clone https://github.com/nitmir/django-cas-server
$ cd django-cas-server
$ pip install -r requirements.txt
```

Then, either run `make install` to create a python package using the sources of the repository and install it with `pip`, or place the `cas_server` directory into your `PYTHONPATH` (for instance by symlinking `cas_server` to the root of your django project).

7. Open `cas_project/settings.py` in your favourite editor and follow the quick start section.

1.4 Quick start

1. Add “cas_server” to your `INSTALLED_APPS` setting like this:

```
INSTALLED_APPS = (  
    'django.contrib.admin',  
    ...  
    'cas_server',  
)
```

For internationalization support, add “`django.middleware.locale.LocaleMiddleware`” to your `MIDDLEWARE` setting like this:

```
MIDDLEWARE = [  
    ...  
    'django.middleware.locale.LocaleMiddleware',  
    ...  
)
```

2. Include the `cas_server` `URLconf` in your project `urls.py` like this:

```
from django.urls import path, include  
  
urlpatterns = [  
    path('admin/', admin.site.urls),  
    ...  
    path('cas/', include('cas_server.urls', namespace="cas_server")),  
)
```

3. Run `python manage.py migrate` to create the `cas_server` models.
4. You should add some management commands to a crontab: `clearsessions`, `cas_clean_tickets` and `cas_clean_sessions`.
 - `clearsessions`: please see [Clearing the session store](#).
 - `cas_clean_tickets`: old tickets and timed-out tickets do not get purged from the database automatically. They are just marked as invalid. `cas_clean_tickets` is a clean-up management command for this purpose. It sends `SingleLogout` requests to services with timed out tickets and deletes them.
 - `cas_clean_sessions`: Logout and purge users (sending `SLO` requests) that are inactive more than `SESSION_COOKIE_AGE`. The default value is 1209600 seconds (2 weeks). You probably should reduce it to something like 86400 seconds (1 day).

You could, for example, do as below:

```
0 0 * * * cas-user /path/to/project/manage.py clearsessions  
*/5 * * * * cas-user /path/to/project/manage.py cas_clean_tickets  
5 0 * * * cas-user /path/to/project/manage.py cas_clean_sessions
```

5. Run `python manage.py createsuperuser` to create an administrator user.
6. Start the development server and visit <http://127.0.0.1:8000/admin/> to add a first service allowed to authenticate user against the CAS (you’ll need the Admin app enabled). See the [Service Patterns](#) section below.
7. Visit <http://127.0.0.1:8000/cas/> to login with your django users.

1.5 Settings

All settings are optional. Add them to `settings.py` to customize `django-cas-server`:

1.5.1 Template settings

- `CAS_LOGO_URL`: URL to the logo shown in the upper left corner on the default template. Set it to `False` to disable it.
- `CAS_FAVICON_URL`: URL to the favicon (shortcut icon) used by the default templates. Default is a key icon. Set it to `False` to disable it.
- `CAS_SHOW_POWERED`: Set it to `False` to hide the powered by footer. The default is `True`.
- `CAS_COMPONENT_URLS`: URLs to css and javascript external components. It is a dictionary having the five following keys: `"bootstrap3_css"`, `"bootstrap3_js"`, `bootstrap4_css`, `bootstrap4_js`, `"html5shiv"`, `"respond"`, `"jquery"`. The default is:

```
{
    "bootstrap3_css": "//maxcdn.bootstrapcdn.com/bootstrap/3.3.6/css/bootstrap.
↪min.css",
    "bootstrap3_js": "//maxcdn.bootstrapcdn.com/bootstrap/3.3.6/js/bootstrap.min.
↪js",
    "html5shiv": "//oss.maxcdn.com/libs/html5shiv/3.7.0/html5shiv.js",
    "respond": "//oss.maxcdn.com/libs/respond.js/1.4.2/respond.min.js",
    "bootstrap4_css": "//stackpath.bootstrapcdn.com/bootstrap/4.4.1/css/bootstrap.
↪min.css",
    "bootstrap4_js": "//stackpath.bootstrapcdn.com/bootstrap/4.4.1/js/bootstrap.
↪min.js",
    "jquery": "//code.jquery.com/jquery.min.js",
}
```

if you omit some keys of the dictionary, the default value for these keys is used.

- `CAS_SHOW_SERVICE_MESSAGES`: Messages displayed about the state of the service on the login page. The default is `True`.
- `CAS_INFO_MESSAGES`: Messages displayed in info-boxes on the html pages of the default templates. It is a dictionary mapping message name to a message dict. A message dict has 3 keys:
 - `message`: A unicode message to display, potentially wrapped around `ugettext_lazy`
 - `discardable`: A boolean, specify if the users can close the message info-box
 - `type`: One of `info`, `success`, `warning`, `danger`. The type of the info-box.

`CAS_INFO_MESSAGES` contains by default one message, `cas_explained`, which explains roughly the purpose of a CAS. The default is:

```
{
    "cas_explained": {
        "message":_(
            u"The Central Authentication Service grants you access to most of our_
↪websites by "
            u"authenticating only once, so you don't need to type your_
↪credentials again unless "
            u"your session expires or you logout."
        ),
```

(continues on next page)

(continued from previous page)

```
        "discardable": True,
        "type": "info", # one of info, success, warning, danger
    },
}
```

- `CAS_INFO_MESSAGES_ORDER`: A list of message names. Order in which info-box messages are displayed. Use an empty list to disable messages display. The default is `[]`.
- `CAS_LOGIN_TEMPLATE`: Path to the template shown on `/login` when the user is not authenticated. The default is `"cas_server/bs4/login.html"`.
- `CAS_WARN_TEMPLATE`: Path to the template shown on `/login?service=...` when the user is authenticated and has asked to be warned before being connected to a service. The default is `"cas_server/bs4/warn.html"`.
- `CAS_LOGGED_TEMPLATE`: Path to the template shown on `/login` when the user is authenticated. The default is `"cas_server/bs4/logged.html"`.
- `CAS_LOGOUT_TEMPLATE`: Path to the template shown on `/logout` when the user is being disconnected. The default is `"cas_server/bs4/logout.html"`.
- `CAS_REDIRECT_TO_LOGIN_AFTER_LOGOUT`: Should we redirect users to `/login` after they logged out instead of displaying `CAS_LOGOUT_TEMPLATE`. The default is `False`.

Note that the old bootstrap3 template is available in `cas_server/bs3/`

1.5.2 Authentication settings

- `CAS_AUTH_CLASS`: A dotted path to a class or a class implementing `cas_server.auth.AuthUser`. The default is `"cas_server.auth.DjangoAuthUser"`. Available classes bundled with `django-cas-server` are listed below in the [Authentication backend](#) section.
- `SESSION_COOKIE_AGE`: This is a django setting. Here, it controls the delay in seconds after which inactive users are logged out. The default is 1209600 (2 weeks). You probably should reduce it to something like 86400 seconds (1 day).
- `CAS_TGT_VALIDITY`: Max time after which the user **MUST** reauthenticate. Set it to *None* for no max time. This can be used to force refreshing cached information only available upon user authentication like the user attributes in federation mode or with the ldap auth in bind mode. The default is *None*.
- `CAS_PROXY_CA_CERTIFICATE_PATH`: Path to certificate authorities file. Usually on linux the local CAs are in `/etc/ssl/certs/ca-certificates.crt`. The default is `True` which tells requests to use its internal certificate authorities. Setting it to `False` should disable all x509 certificate validation and **MUST** not be done in production. x509 certificate validation is performed upon PGT issuance.
- `CAS_SLO_MAX_PARALLEL_REQUESTS`: Maximum number of parallel single log out requests sent. If more requests need to be sent, they are queued. The default is 10.
- `CAS_SLO_TIMEOUT`: Timeout for a single SLO request in seconds. The default is 5.
- `CAS_REMOVE_DJANGO_SESSION_COOKIE_ON_LOGOUT`: If *True* Django session cookie will be removed on logout from CAS server (default *False*). Note that Django session middleware will generate a new session cookie.
- `CAS_REMOVE_DJANGO_CSRF_COOKIE_ON_LOGOUT`: If *True* Django csrf cookie will be removed on logout from CAS server (default *False*). Note that Django csrf middleware will generate a new csrf token cookie.
- `CAS_REMOVE_DJANGO_LANGUAGE_COOKIE_ON_LOGOUT`: If *True* Django language cookie will be removed on logout from CAS server (default *False*).

1.5.3 Federation settings

- `CAS_FEDERATE`: A boolean for activating the federated mode (see the *Federation mode* section below). The default is `False`.
- `CAS_FEDERATE_REMEMBER_TIMEOUT`: Time after which the cookie used for “remember my identity provider” expire. The default is 604800, one week. The cookie is called `_remember_provider`.

1.5.4 New version warnings settings

- `CAS_NEW_VERSION_HTML_WARNING`: A boolean for displaying a warning on html pages that a new version of the application is available. Once closed by a user, it is not displayed to this user until the next new version. The default is `True`.
- `CAS_NEW_VERSION_EMAIL_WARNING`: A boolean for sending a email to `settings.ADMINS` when a new version is available. The default is `True`.

1.5.5 Tickets validity settings

- `CAS_TICKET_VALIDITY`: Number of seconds the service tickets and proxy tickets are valid. This is the maximal time between ticket issuance by the CAS and ticket validation by an application. The default is 60.
- `CAS_PGT_VALIDITY`: Number of seconds the proxy granting tickets are valid. The default is 3600 (1 hour).
- `CAS_TICKET_TIMEOUT`: Number of seconds a ticket is kept in the database before sending Single Log Out request and being cleared. The default is 86400 (24 hours).

1.5.6 Tickets miscellaneous settings

- `CAS_TICKET_LEN`: Default ticket length. All CAS implementations **MUST** support ST and PT up to 32 chars, PGT and PGTIU up to 64 chars and it is **RECOMMENDED** that all tickets up to 256 chars are supported. Here the default is 64.
- `CAS_LT_LEN`: Length of the login tickets. Login tickets are only processed by django-cas-server thus there are no length restrictions on it. The default is `CAS_TICKET_LEN`.
- `CAS_ST_LEN`: Length of the service tickets. The default is `CAS_TICKET_LEN`. You may need to lower it to 32 if you use some old clients.
- `CAS_PT_LEN`: Length of the proxy tickets. The default is `CAS_TICKET_LEN`. This length should be the same as `CAS_ST_LEN`. You may need to lower it to 32 if you use some old clients.
- `CAS_PGT_LEN`: Length of the proxy granting tickets. The default is `CAS_TICKET_LEN`.
- `CAS_PGTIU_LEN`: Length of the proxy granting tickets IOU. The default is `CAS_TICKET_LEN`.
- `CAS_LOGIN_TICKET_PREFIX`: Prefix of login tickets. The default is "LT".
- `CAS_SERVICE_TICKET_PREFIX`: Prefix of service tickets. The default is "ST". The CAS specification mandates that service tickets **MUST** begin with the characters ST so you should not change this.
- `CAS_PROXY_TICKET_PREFIX`: Prefix of proxy ticket. The default is "PT".
- `CAS_PROXY_GRANTING_TICKET_PREFIX`: Prefix of proxy granting ticket. The default is "PGT".
- `CAS_PROXY_GRANTING_TICKET_IU_PREFIX`: Prefix of proxy granting ticket IOU. The default is "PGTIU".

1.5.7 Mysql backend settings

Deprecated, see the *Sql backend settings*. Only useful if you are using the mysql authentication backend:

- `CAS_SQL_HOST`: Host for the SQL server. The default is `"localhost"`.
- `CAS_SQL_USERNAME`: Username for connecting to the SQL server.
- `CAS_SQL_PASSWORD`: Password for connecting to the SQL server.
- `CAS_SQL_DBNAME`: Database name.
- `CAS_SQL_DBCHARSET`: Database charset. The default is `"utf8"`.
- `CAS_SQL_USER_QUERY`: The query performed upon user authentication. The username must be in field `username`, the password in `password`, additional fields are used as the user attributes. The default is `"SELECT user AS username, pass AS password, users.* FROM users WHERE user = %s"`.
- `CAS_SQL_PASSWORD_CHECK`: The method used to check the user password. Must be one of the following:
 - `"crypt"` (see <[https://en.wikipedia.org/wiki/Crypt_\(C\)](https://en.wikipedia.org/wiki/Crypt_(C))>), the password in the database should begin with `$`
 - `"ldap"` (see <https://tools.ietf.org/id/draft-stroeder-hashed-userpassword-values-01.html>) the password in the database must begin with one of {MD5}, {SMD5}, {SHA}, {SSHA}, {SHA256}, {SSHA256}, {SHA384}, {SSHA384}, {SHA512}, {SSHA512}, {CRYPT}.
 - `"hex_HASH_NAME"` with `HASH_NAME` in `md5`, `sha1`, `sha224`, `sha256`, `sha384`, `sha512`. The hashed password in the database is compared to the hexadecimal digest of the clear password hashed with the corresponding algorithm.
 - `"plain"`, the password in the database must be in clear.

The default is `"crypt"`.

1.5.8 Sql backend settings

Only useful if you are using the sql authentication backend. You must add a `"cas_server"` database to `settings.DATABASES` as defined in the django documentation. It is then the database used by the sql backend.

- `CAS_SQL_USER_QUERY`: The query performed upon user authentication. The username must be in field `username`, the password in `password`, additional fields are used as the user attributes. The default is `"SELECT user AS username, pass AS password, users.* FROM users WHERE user = %s"`.
- `CAS_SQL_PASSWORD_CHECK`: The method used to check the user password. Must be one of the following:
 - `"crypt"` (see <[https://en.wikipedia.org/wiki/Crypt_\(C\)](https://en.wikipedia.org/wiki/Crypt_(C))>), the password in the database should begin with `$`
 - `"ldap"` (see <https://tools.ietf.org/id/draft-stroeder-hashed-userpassword-values-01.html>) the password in the database must begin with one of {MD5}, {SMD5}, {SHA}, {SSHA}, {SHA256}, {SSHA256}, {SHA384}, {SSHA384}, {SHA512}, {SSHA512}, {CRYPT}.
 - `"hex_HASH_NAME"` with `HASH_NAME` in `md5`, `sha1`, `sha224`, `sha256`, `sha384`, `sha512`. The hashed password in the database is compared to the hexadecimal digest of the clear password hashed with the corresponding algorithm.
 - `"plain"`, the password in the database must be in clear.

The default is `"crypt"`.

- `CAS_SQL_PASSWORD_CHARSET`: Charset the SQL users passwords was hash with. This is needed to encode the user submitted password before hashing it for comparison. The default is `"utf-8"`.

1.5.9 Ldap backend settings

Only useful if you are using the ldap authentication backend:

- `CAS_LDAP_SERVER`: Address of the LDAP server. The default is `"localhost"`.
- `CAS_LDAP_USER`: User bind address, for example `"cn=admin,dc=crans,dc=org"` for connecting to the LDAP server.
- `CAS_LDAP_PASSWORD`: Password for connecting to the LDAP server.
- `CAS_LDAP_BASE_DN`: LDAP search base DN, for example `"ou=data,dc=crans,dc=org"`.
- `CAS_LDAP_USER_QUERY`: Search filter for searching user by username. User entered usernames are escaped using `ldap3.utils.conv.escape_bytes`. The default is `"(uid=%s)"`
- `CAS_LDAP_USERNAME_ATTR`: Attribute used for user's usernames. The default is `"uid"`
- `CAS_LDAP_PASSWORD_ATTR`: Attribute used for user's passwords. The default is `"userPassword"`
- `CAS_LDAP_PASSWORD_CHECK`: The method used to check the user password. Must be one of the following:
 - `"crypt"` (see [https://en.wikipedia.org/wiki/Crypt_\(C\)](https://en.wikipedia.org/wiki/Crypt_(C))), the password in the database should begin with `$`
 - `"ldap"` (see <https://tools.ietf.org/id/draft-stroeder-hashed-userpassword-values-01.html>) the password in the database must begin with one of `{MD5}`, `{SMD5}`, `{SHA}`, `{SSHA}`, `{SHA256}`, `{SSHA256}`, `{SHA384}`, `{SSHA384}`, `{SHA512}`, `{SSHA512}`, `{CRYPT}`.
 - `"hex_HASH_NAME"` with `HASH_NAME` in `md5`, `sha1`, `sha224`, `sha256`, `sha384`, `sha512`. The hashed password in the database is compared to the hexadecimal digest of the clear password hashed with the corresponding algorithm.
 - `"plain"`, the password in the database must be in clear.
 - `"bind"`, the user credentials are used to bind to the ldap database and retrieve the user attribute. In this mode, the settings `CAS_LDAP_PASSWORD_ATTR` and `CAS_LDAP_PASSWORD_CHARSET` are ignored, and it is the ldap server that performs the password check.

The default is `"ldap"`.

- `CAS_LDAP_ATTRS_VIEW`: This parameter is only used then `CAS_LDAP_PASSWORD_CHECK` is set to `"bind"`. If 0 the user attributes are retrieved by connecting to the ldap as `CAS_LDAP_USER`. If 1 the user attributes are retrieve then the user authenticate using the user credentials and are cached for later use. It means there can be some differences between the attributes in database and the cached ones. See the parameter `CAS_TGT_VALIDITY` to force user to reauthenticate periodically. The default is 0.
- `CAS_LDAP_PASSWORD_CHARSET`: Charset the LDAP users passwords was hashed with. This is needed to encode the user submitted password before hashing it for comparison. The default is `"utf-8"`.

1.5.10 Test backend settings

Only useful if you are using the test authentication backend:

- `CAS_TEST_USER`: Username of the test user. The default is `"test"`.
- `CAS_TEST_PASSWORD`: Password of the test user. The default is `"test"`.

- `CAS_TEST_ATTRIBUTES`: Attributes of the test user. The default is `{'nom': 'Nymous', 'prenom': 'Ano', 'email': 'anonymous@example.net', 'alias': ['demo1', 'demo2']}`.

1.6 Authentication backend

django-cas-server comes with some authentication backends:

- dummy backend `cas_server.auth.DummyAuthUser`: all authentication attempts fail.
- test backend `cas_server.auth.TestAuthUser`: username, password and returned attributes for the user are defined by the `CAS_TEST_*` settings.
- django backend `cas_server.auth.DjangoAuthUser`: Users are authenticated against django users system. This is the default backend. The returned attributes are the fields available on the user model.
- mysql backend `cas_server.auth.MysqlAuthUser`: Deprecated, use the sql backend instead. see the *Mysql backend settings* section. The returned attributes are those returned by sql query `CAS_SQL_USER_QUERY`.
- sql backend `cas_server.auth.SqlAuthUser`: see the *Sql backend settings* section. The returned attributes are those returned by sql query `CAS_SQL_USER_QUERY`.
- ldap backend `cas_server.auth.LdapAuthUser`: see the *Ldap backend settings* section. The returned attributes are those of the ldap node returned by the query filter `CAS_LDAP_USER_QUERY`.
- federated backend `cas_server.auth.CASFederateAuth`: It is automatically used when `CAS_FEDERATE` is `True`. You should not set it manually without setting `CAS_FEDERATE` to `True`.

1.7 Logs

django-cas-server logs most of its actions. To enable login, you must set the `LOGGING` (<https://docs.djangoproject.com/en/stable/topics/logging>) variable in `settings.py`.

Users successful actions (login, logout) are logged with the level `INFO`, failures are logged with the level `WARNING` and user attributes transmitted to a service are logged with the level `DEBUG`.

For example to log to syslog you can use :

```
LOGGING = {
    'version': 1,
    'disable_existing_loggers': False,
    'formatters': {
        'cas_syslog': {
            'format': 'cas: %(levelname)s %(message)s'
        },
    },
    'handlers': {
        'cas_syslog': {
            'level': 'INFO',
            'class': 'logging.handlers.SysLogHandler',
            'address': '/dev/log',
            'formatter': 'cas_syslog',
        },
    },
    'loggers': {
```

(continues on next page)

(continued from previous page)

```

        'cas_server': {
            'handlers': ['cas_syslog'],
            'level': 'INFO',
            'propagate': True,
        },
    },
}

```

Or to log to a file:

```

LOGGING = {
    'version': 1,
    'disable_existing_loggers': False,
    'formatters': {
        'cas_file': {
            'format': '%(asctime)s %(levelname)s %(message)s'
        },
    },
    'handlers': {
        'cas_file': {
            'level': 'INFO',
            'class': 'logging.FileHandler',
            'filename': '/tmp/cas_server.log',
            'formatter': 'cas_file',
        },
    },
    'loggers': {
        'cas_server': {
            'handlers': ['cas_file'],
            'level': 'INFO',
            'propagate': True,
        },
    },
}

```

1.8 Service Patterns

In a CAS context, *Service* refers to the application the client is trying to access. By extension we use *service* for the URL of such an application.

By default, `django-cas-server` does not allow any service to use the CAS to authenticate users. In order to allow services, you need to connect to the django admin interface using a django superuser, and add a first service pattern.

A service pattern comes with 9 fields:

- **Position:** an integer used to change the order in which services are matched against service patterns.
- **Name:** the name of the service pattern. It will be displayed to the users asking for a ticket for a service matching this service pattern on the login page.
- **Pattern:** a regular expression used to match services.
- **User field:** the user attribute to use as username for services matching this service pattern. Leave it empty to use the login name.
- **Restrict username:** if checked, only login names defined below are allowed to get tickets for services matching this service pattern.

- `Proxy`: if checked, allow the creation of Proxy Ticket for services matching this service pattern. Otherwise, only Service Ticket will be created.
- `Proxy callback`: if checked, services matching this service pattern are allowed to retrieve Proxy Granting Ticket. A service with a Proxy Granting Ticket can get Proxy Ticket for other services. Hence you must only check this for trusted services that need it. (For instance, a webmail needs Proxy Ticket to authenticate himself as the user to the imap server).
- `Single log out`: Check it to send Single Log Out requests to authenticated services matching this service pattern. SLO requests are sent to all services the user is authenticated to when the user disconnects.
- `Single log out callback`: The http(s) URL to POST the SLO requests. If empty, the service URL is used. This field is useful to allow non http services (imap, smtp, ftp) to handle SLO requests.

A service pattern has 4 associated models:

- `Username`s: a list of username associated with the `Restrict username` field
- `Replace attribute names`: a list of user attributes to send to the service. Choose the name used for sending the attribute by setting `Replacement` or leave it empty to leave it unchanged.
- `Replace attribute values`: a list of sent user attributes for which value needs to be tweaked. Replace the attribute value by the string obtained by replacing the leftmost non-overlapping occurrences of `pattern` in string by `replace`. In `replace` backslash escapes are processed. Matched groups are captured by 1, 2, etc.
- `Filter attribute values`: a list of user attributes for which value needs to match a regular expression. For instance, service A may need an email address, and you only want user with an email address to connect to it. To do so, put `email` in `Attribute` and `.*` in `pattern`.

When a user asks for a ticket for a service, the service URL is compared against each service pattern sorted by `position`. The first service pattern that matches the service URL is chosen. Hence, you should give low `position` to very specific patterns like `^https://www\.example\.com(/.*)?$` and higher `position` to generic patterns like `^https://.*`. So the service URL `https://www.example.com` will use the service pattern for `^https://www\.example\.com(/.*)?$` and not the one for `^https://.*`.

1.9 Federation mode

`django-cas-server` comes with a federation mode. When `CAS_FEDERATE` is `True`, users are invited to choose an identity provider on the login page, then, they are redirected to the provider CAS to authenticate. This provider transmits to `django-cas-server` the user username and attributes. The user is now logged in on `django-cas-server` and can use services using `django-cas-server` as CAS.

In federation mode, the user attributes are cached upon user authentication. See the settings `CAS_TGT_VALIDITY` to force users to reauthenticate periodically and allow `django-cas-server` to refresh cached attributes.

The list of allowed identity providers is defined using the django admin application. With the development server started, visit <http://127.0.0.1:8000/admin/> to add identity providers.

An identity provider comes with 5 fields:

- `Position`: an integer used to tweak the order in which identity providers are displayed on the login page. Identity providers are sorted using `position` first, then, on equal `position`, using `verbose name` and then, on equal `verbose name`, using `suffix`.
- `Suffix`: the suffix that will be append to the username returned by the identity provider. It must be unique.
- `Server url`: the URL to the identity provider CAS. For instance, if you are using `https://cas.example.org/login` to authenticate on the CAS, the `server url` is `https://cas.example.org`

- `CAS protocol version`: the version of the CAS protocol to use to contact the identity provider. The default is version 3.
- `Verbose name`: the name used on the login page to display the identity provider.
- `Display`: a boolean controlling the display of the identity provider on the login page. Beware that this do not disable the identity provider, it just hide it on the login page. User will always be able to log in using this provider by fetching `/federate/provider_suffix`.

In federation mode, `django-cas-server` build user's username as follow: `provider_returned_username@provider_suffix`. Choose the provider returned username for `django-cas-server` and the provider suffix in order to make sense, as this built username is likely to be displayed to end users in applications.

Then using federate mode, you should add one command to a daily crontab: `cas_clean_federate`. This command clean the local cache of federated user from old unused users.

You could for example do as below:

```
10 0 * * * cas-user /path/to/project/manage.py cas_clean_federate
```


2.1 Subpackages

2.1.1 cas_server.templatetags package

Submodules

cas_server.templatetags.cas_server module

template tags for the app

`cas_server.templatetags.cas_server.is_checkbox` (*field*)

check if a form bound field is a checkbox

Parameters `field` (*django.forms.BoundField*) – A bound field

Returns True if the field is a checkbox, False otherwise.

Return type bool

`cas_server.templatetags.cas_server.is_hidden` (*field*)

check if a form bound field is hidden

Parameters `field` (*django.forms.BoundField*) – A bound field

Returns True if the field is hidden, False otherwise.

Return type bool

Module contents

2.2 Submodules

2.2.1 cas_server.admin module

module for the admin interface of the app

class cas_server.admin.**BaseInlines** (*parent_model, admin_site*)
Bases: `django.contrib.admin.TabularInline`

Base class for inlines in the admin interface.

extra = 0

This controls the number of extra forms the formset will display in addition to the initial forms.

media

class cas_server.admin.**UserAdminInlines** (*parent_model, admin_site*)
Bases: `BaseInlines`

Base class for inlines in `UserAdmin` interface

form

alias of `cas_server.forms.TicketForm`

readonly_fields = ('validate', 'service', 'service_pattern', 'creation', 'renew', 'single_log_o

Fields to display on a object that are read only (not editable).

fields = ('validate', 'service', 'service_pattern', 'creation', 'renew', 'single_log_o

Fields to display on a object.

media

class cas_server.admin.**ServiceTicketInline** (*parent_model, admin_site*)
Bases: `UserAdminInlines`

`ServiceTicket` in admin interface

model

alias of `cas_server.models.ServiceTicket`

media

class cas_server.admin.**ProxyTicketInline** (*parent_model, admin_site*)
Bases: `UserAdminInlines`

`ProxyTicket` in admin interface

model

alias of `cas_server.models.ProxyTicket`

media

class cas_server.admin.**ProxyGrantingInline** (*parent_model, admin_site*)
Bases: `UserAdminInlines`

`ProxyGrantingTicket` in admin interface

model

alias of `cas_server.models.ProxyGrantingTicket`

media


```
class cas_server.admin.UserAdmin (model, admin_site)
    Bases: django.contrib.admin.ModelAdmin

    User in admin interface

    inlines = (<class 'cas_server.admin.ServiceTicketInline'>, <class 'cas_server.admin.Pr
        See ServiceTicketInline, ProxyTicketInline, ProxyGrantingInline objects below
        the UserAdmin fields.

    readonly_fields = ('username', 'date', 'session_key')
        Fields to display on a object that are read only (not editable).

    fields = ('username', 'date', 'session_key')
        Fields to display on a object.

    list_display = ('username', 'date', 'session_key')
        Fields to display on the list of class:UserAdmin objects.

    media

class cas_server.admin.UnamesInline (parent_model, admin_site)
    Bases: BaseInlines

    Username in admin interface

    model
        alias of cas_server.models.Username

    media

class cas_server.admin.ReplaceAttributNameInline (parent_model, admin_site)
    Bases: BaseInlines

    ReplaceAttributName in admin interface

    model
        alias of cas_server.models.ReplaceAttributName

    media

class cas_server.admin.ReplaceAttributValueInline (parent_model, admin_site)
    Bases: BaseInlines

    ReplaceAttributValue in admin interface

    model
        alias of cas_server.models.ReplaceAttributValue

    media

class cas_server.admin.FilterAttributValueInline (parent_model, admin_site)
    Bases: BaseInlines

    FilterAttributValue in admin interface

    model
        alias of cas_server.models.FilterAttributValue

    media

class cas_server.admin.ServicePatternAdmin (model, admin_site)
    Bases: django.contrib.admin.ModelAdmin

    ServicePattern in admin interface
```

`inlines = (<class 'cas_server.admin.UsernamesInline'>, <class 'cas_server.admin.ReplaceAttributeInline'>, <class 'cas_server.admin.ReplaceAttributeValueInline'>, <class 'cas_server.admin.FilterAttributeValueInline'>)`
See *UsernamesInline*, *ReplaceAttributeInline*, *ReplaceAttributeValueInline*, *FilterAttributeValueInline* objects below the *ServicePatternAdmin* fields.

`list_display = ('pos', 'name', 'pattern', 'proxy', 'single_log_out', 'proxy_callback', 'display')`
Fields to display on the list of class:*ServicePatternAdmin* objects.

`media`

`class cas_server.admin.FederatedIdentityProviderAdmin(model, admin_site)`

Bases: `django.contrib.admin.ModelAdmin`

FederatedIdentityProvider in admin interface

`fields = ('pos', 'suffix', 'server_url', 'cas_protocol_version', 'verbose_name', 'display')`
Fields to display on a object.

`list_display = ('verbose_name', 'suffix', 'display')`
Fields to display on the list of class:*FederatedIdentityProviderAdmin* objects.

`media`

`class cas_server.admin.FederatedUserAdmin(model, admin_site)`

Bases: `django.contrib.admin.ModelAdmin`

FederatedUser in admin interface

`fields = ('username', 'provider', 'last_update')`
Fields to display on a object.

`list_display = ('username', 'provider', 'last_update')`
Fields to display on the list of class:*FederatedUserAdmin* objects.

`media`

`class cas_server.admin.UserAttributesAdmin(model, admin_site)`

Bases: `django.contrib.admin.ModelAdmin`

UserAttributes in admin interface

`fields = ('username', '_attributes')`
Fields to display on a object.

`media`

2.2.2 cas_server.apps module

django config module

`class cas_server.apps.CasAppConfig(app_name, app_module)`

Bases: `django.apps.AppConfig`

django CAS application config class

`name = 'cas_server'`

Full Python path to the application. It must be unique across a Django project.

`verbose_name = 'Central Authentication Service'`

Human-readable name for the application.

2.2.3 cas_server.auth module

Some authentication classes for the CAS

class cas_server.auth.AuthUser(*username*)

Bases: `object`

Authentication base class

Parameters *username* (*unicode*) – A username, stored in the *username* class attribute.

username = `None`

username used to instantiate the current object

test_password(*password*)

Tests *password* against the user-supplied password.

Raises `NotImplementedError` – always. The method need to be implemented by sub-classes

attributs()

The user attributes.

raises `NotImplementedError`: always. The method need to be implemented by subclasses

class cas_server.auth.DummyAuthUser(*username*)

Bases: `cas_server.auth.AuthUser`

A Dummy authentication class. Authentication always fails

Parameters *username* (*unicode*) – A username, stored in the *username* class attribute. There is no valid value for this attribute here.

test_password(*password*)

Tests *password* against the user-supplied password.

Parameters *password* (*unicode*) – a clear text password as submitted by the user.

Returns always `False`

Return type `bool`

attributs()

The user attributes.

Returns an empty `dict`.

Return type `dict`

class cas_server.auth.TestAuthUser(*username*)

Bases: `cas_server.auth.AuthUser`

A test authentication class only working for one unique user.

Parameters *username* (*unicode*) – A username, stored in the *username* class attribute. The uniq valid value is `settings.CAS_TEST_USER`.

test_password(*password*)

Tests *password* against the user-supplied password.

Parameters *password* (*unicode*) – a clear text password as submitted by the user.

Returns `True` if *username* is valid and *password* is equal to `settings.CAS_TEST_PASSWORD`, `False` otherwise.

Return type `bool`

attributs()

The user attributes.

Returns the settings.CAS_TEST_ATTRIBUTES dict if *username* is valid, an empty dict otherwise.

Return type dict

class cas_server.auth.DBAuthUser(*username*)

Bases: cas_server.auth.AuthUser

base class for databate based auth classes

user = None

DB user attributes as a dict if the username is found in the database.

attributs()

The user attributes.

Returns a dict with the user attributes. Attributes may be unicode() or list of unicode(). If the user do not exists, the returned dict is empty.

Return type dict

class cas_server.auth.MySqlAuthUser(*username*)

Bases: cas_server.auth.DBAuthUser

DEPRECATED, use SqlAuthUser instead.

A mysql authentication class: authenticate user against a mysql database

Parameters *username* (unicode) – A username, stored in the *username* class attribute. Valid value are fetched from the MySQL database set with settings.CAS_SQL_* settings parameters using the query settings.CAS_SQL_USER_QUERY.

test_password(*password*)

Tests password against the user-supplied password.

Parameters *password* (unicode) – a clear text password as submitted by the user.

Returns True if *username* is valid and password is correct, False otherwise.

Return type bool

class cas_server.auth.SqlAuthUser(*username*)

Bases: cas_server.auth.DBAuthUser

A SQL authentication class: authenticate user against a SQL database. The SQL database must be configures in settings.py as settings.DATABASES['cas_server'].

Parameters *username* (unicode) – A username, stored in the *username* class attribute. Valid value are fetched from the MySQL database set with settings.CAS_SQL_* settings parameters using the query settings.CAS_SQL_USER_QUERY.

test_password(*password*)

Tests password against the user-supplied password.

Parameters *password* (unicode) – a clear text password as submitted by the user.

Returns True if *username* is valid and password is correct, False otherwise.

Return type bool

class cas_server.auth.LdapAuthUser(*username*)

Bases: cas_server.auth.DBAuthUser

A ldap authentication class: authenticate user against a ldap database

Parameters `username` (*unicode*) – A username, stored in the `username` class attribute. Valid value are fetched from the ldap database set with `settings.CAS_LDAP_*` settings parameters.

classmethod `get_conn()`

Return a connection object to the ldap database

test_password (*password*)

Tests `password` against the user-supplied password.

Parameters `password` (*unicode*) – a clear text password as submitted by the user.

Returns `True` if `username` is valid and `password` is correct, `False` otherwise.

Return type `bool`

attributes ()

The user attributes.

Returns a `dict` with the user attributes. Attributes may be `unicode()` or `list` of `unicode()`. If the user do not exists, the returned `dict` is empty.

Return type `dict`

class `cas_server.auth.DjangoAuthUser` (*username*)

Bases: `cas_server.auth.AuthUser`

A django auth class: authenticate user against django internal users

Parameters `username` (*unicode*) – A username, stored in the `username` class attribute. Valid value are usernames of django internal users.

user = `None`

a django user object if the username is found. The user model is retrieved using `django.contrib.auth.get_user_model()`.

test_password (*password*)

Tests `password` against the user-supplied password.

Parameters `password` (*unicode*) – a clear text password as submitted by the user.

Returns `True` if `user` is valid and `password` is correct, `False` otherwise.

Return type `bool`

attributes ()

The user attributes, defined as the fields on the `user` object.

Returns a `dict` with the `user` object fields. Attributes may be If the user do not exists, the returned `dict` is empty.

Return type `dict`

class `cas_server.auth.CASFederateAuth` (*username*)

Bases: `cas_server.auth.AuthUser`

Authentication class used then `CAS_FEDERATE` is `True`

Parameters `username` (*unicode*) – A username, stored in the `username` class attribute. Valid value are usernames of `FederatedUser` object. `FederatedUser` object are created on CAS backends successful ticket validation.

user = `None`

a `:class'FederatedUser<cas_server.models.FederatedUser>'` object if `username` is found.

test_password (*ticket*)

Tests password against the user-supplied password.

Parameters **password** (*unicode*) – The CAS tickets just used to validate the user authentication against its CAS backend.

Returns True if *user* is valid and password is a ticket validated less than `settings.CAS_TICKET_VALIDITY` seconds and has not being previously used for authenticated this *FederatedUser*. False otherwise.

Return type `bool`

attributes ()

The user attributes, as returned by the CAS backend.

Returns *FederatedUser.attributes*. If the user do not exists, the returned `dict` is empty.

Return type `dict`

2.2.4 cas_server.cas module

exception `cas_server.cas.CASError`

Bases: `ValueError`

class `cas_server.cas.ReturnUnicode`

Bases: `object`

static u (*string, charset*)

class `cas_server.cas.SingleLogoutMixin`

Bases: `object`

classmethod `get_saml_slos` (*logout_request*)

returns saml logout ticket info

class `cas_server.cas.CASClient`

Bases: `object`

class `cas_server.cas.CASClientBase` (*service_url=None, server_url=None, ex-
tra_login_params=None, renew=False, user-
name_attribute=None*)

Bases: `object`

logout_redirect_param_name = `'service'`

verify_ticket (*ticket*)

must return a triple

get_login_url ()

Generates CAS login URL

get_logout_url (*redirect_url=None*)

Generates CAS logout URL

get_proxy_url (*pgt*)

Returns proxy url, given the proxy granting ticket

get_proxy_ticket (*pgt*)

Returns proxy ticket given the proxy granting ticket

static get_page_charset (*page, default='utf-8'*)

```

class cas_server.cas.CASClientV1 (service_url=None,          server_url=None,          ex-
                                tra_login_params=None,      renew=False,          user-
                                name_attribute=None)
Bases: cas_server.cas.CASClientBase, cas_server.cas.ReturnUnicode
CAS Client Version 1

logout_redirect_param_name = 'url'

verify_ticket (ticket)
    Verifies CAS 1.0 authentication ticket.

    Returns username on success and None on failure.

class cas_server.cas.CASClientV2 (proxy_callback=None, *args, **kwargs)
Bases: cas_server.cas.CASClientBase, cas_server.cas.ReturnUnicode
CAS Client Version 2

url_suffix = 'serviceValidate'

logout_redirect_param_name = 'url'

verify_ticket (ticket)
    Verifies CAS 2.0+/3.0+ XML-based authentication ticket and returns extended attributes

get_verification_response (ticket)

classmethod parse_attributes_xml_element (element, charset)

classmethod verify_response (response, charset)

classmethod parse_response_xml (response, charset)

class cas_server.cas.CASClientV3 (proxy_callback=None, *args, **kwargs)
Bases: cas_server.cas.CASClientV2, cas_server.cas.SingleLogoutMixin
CAS Client Version 3

url_suffix = 'serviceValidate'

logout_redirect_param_name = 'service'

classmethod parse_attributes_xml_element (element, charset)

classmethod verify_response (response, charset)

class cas_server.cas.CASClientWithSAMLV1 (proxy_callback=None, *args, **kwargs)
Bases: cas_server.cas.CASClientV2, cas_server.cas.SingleLogoutMixin
CASClient 3.0+ with SAML

verify_ticket (ticket, **kwargs)
    Verifies CAS 3.0+ XML-based authentication ticket and returns extended attributes.

    @date: 2011-11-30 @author: Carlos Gonzalez Vila <carlewis@gmail.com>

    Returns username and attributes on success and None,None on failure.

fetch_saml_validation (ticket)

classmethod get_saml_assertion (ticket)
    http://www.jasig.org/cas/protocol#samlvalidate-cas-3.0

    SAML request values:

    RequestID [REQUIRED]: unique identifier for the request

    IssueInstant [REQUIRED]: timestamp of the request

```

samlp:AssertionArtifact [REQUIRED]: the valid CAS Service Ticket obtained as a response parameter at login.

2.2.5 cas_server.default_settings module

Default values for the app's settings

`cas_server.default_settings.CAS_LOGO_URL = '/static/cas_server/logo.png'`
URL to the logo showed in the up left corner on the default templates.

`cas_server.default_settings.CAS_FAVICON_URL = '/static/cas_server/favicon.ico'`
URL to the favicon (shortcut icon) used by the default templates. Default is a key icon.

`cas_server.default_settings.CAS_SHOW_POWERED = True`
Show the powered by footer if set to True

`cas_server.default_settings.CAS_COMPONENT_URLS = {'bootstrap3_css': '//maxcdn.bootstrapcdn.com/bootstrap/3.3.7/css/bootstrap.min.css'}`
URLs to css and javascript external components.

`cas_server.default_settings.CAS_LOGIN_TEMPLATE = 'cas_server/bs4/login.html'`
Path to the template showed on /login then the user is not authenticated.

`cas_server.default_settings.CAS_WARN_TEMPLATE = 'cas_server/bs4/warn.html'`
Path to the template showed on /login?service=... then the user is authenticated and has asked to be warned before being connected to a service.

`cas_server.default_settings.CAS_LOGGED_TEMPLATE = 'cas_server/bs4/logged.html'`
Path to the template showed on /login then to user is authenticated.

`cas_server.default_settings.CAS_LOGOUT_TEMPLATE = 'cas_server/bs4/logout.html'`
Path to the template showed on /logout then to user is being disconnected.

`cas_server.default_settings.CAS_REDIRECT_TO_LOGIN_AFTER_LOGOUT = False`
Should we redirect users to /login after they logged out instead of displaying `CAS_LOGOUT_TEMPLATE`.

`cas_server.default_settings.CAS_AUTH_CLASS = 'cas_server.auth.DjangoAuthUser'`
A dotted path to a class or a class implementing `cas_server.auth.AuthUser`.

`cas_server.default_settings.CAS_PROXY_CA_CERTIFICATE_PATH = True`
Path to certificate authorities file. Usually on linux the local CAs are in `/etc/ssl/certs/ca-certificates.crt`. True tell requests to use its internal certificate authorities.

`cas_server.default_settings.CAS_SLO_MAX_PARALLEL_REQUESTS = 10`
Maximum number of parallel single log out requests send if more requests need to be send, there are queued

`cas_server.default_settings.CAS_SLO_TIMEOUT = 5`
Timeout for a single SLO request in seconds.

`cas_server.default_settings.CAS_AUTH_SHARED_SECRET = ''`
Shared to transmit then using the view `cas_server.views.Auth`

`cas_server.default_settings.CAS_TGT_VALIDITY = None`
Max time after with the user MUST reauthenticate. Let it to *None* for no max time. This can be used to force refreshing cached informations only available upon user authentication like the user attributes in federation mode or with the ldap auth in bind mode.

`cas_server.default_settings.CAS_TICKET_VALIDITY = 60`
Number of seconds the service tickets and proxy tickets are valid. This is the maximal time between ticket issuance by the CAS and ticket validation by an application.

`cas_server.default_settings.CAS_PGT_VALIDITY = 3600`
Number of seconds the proxy granting tickets are valid.

`cas_server.default_settings.CAS_TICKET_TIMEOUT = 86400`

Number of seconds a ticket is kept in the database before sending Single Log Out request and being cleared.

`cas_server.default_settings.CAS_TICKET_LEN = 64`

All CAS implementation MUST support ST and PT up to 32 chars, PGT and PGTIU up to 64 chars and it is RECOMMENDED that all tickets up to 256 chars are supported so we use 64 for the default len.

`cas_server.default_settings.CAS_LT_LEN = 64`

alias of settings.CAS_TICKET_LEN

`cas_server.default_settings.CAS_ST_LEN = 64`

alias of settings.CAS_TICKET_LEN Services MUST be able to accept service tickets of up to 32 characters in length.

`cas_server.default_settings.CAS_PT_LEN = 64`

alias of settings.CAS_TICKET_LEN Back-end services MUST be able to accept proxy tickets of up to 32 characters.

`cas_server.default_settings.CAS_PGT_LEN = 64`

alias of settings.CAS_TICKET_LEN Services MUST be able to handle proxy-granting tickets of up to 64

`cas_server.default_settings.CAS_PGTIU_LEN = 64`

alias of settings.CAS_TICKET_LEN Services MUST be able to handle PGTIUs of up to 64 characters in length.

`cas_server.default_settings.CAS_LOGIN_TICKET_PREFIX = 'LT'`

Prefix of login tickets.

`cas_server.default_settings.CAS_SERVICE_TICKET_PREFIX = 'ST'`

Prefix of service tickets. Service tickets MUST begin with the characters ST so you should not change this.

`cas_server.default_settings.CAS_PROXY_TICKET_PREFIX = 'PT'`

Prefix of proxy ticket. Proxy tickets SHOULD begin with the characters, PT.

`cas_server.default_settings.CAS_PROXY_GRANTING_TICKET_PREFIX = 'PGT'`

Prefix of proxy granting ticket. Proxy-granting tickets SHOULD begin with the characters PGT.

`cas_server.default_settings.CAS_PROXY_GRANTING_TICKET_IOU_PREFIX = 'PGTIU'`

Prefix of proxy granting ticket IOU. Proxy-granting ticket IOUs SHOULD begin with the characters PGTIU.

`cas_server.default_settings.CAS_SQL_HOST = 'localhost'`

Host for the SQL server.

`cas_server.default_settings.CAS_SQL_USERNAME = ''`

Username for connecting to the SQL server.

`cas_server.default_settings.CAS_SQL_PASSWORD = ''`

Password for connecting to the SQL server.

`cas_server.default_settings.CAS_SQL_DBNAME = ''`

Database name.

`cas_server.default_settings.CAS_SQL_DBCHARSET = 'utf8'`

Database charset.

`cas_server.default_settings.CAS_SQL_USER_QUERY = 'SELECT user AS username, pass AS password'`

The query performed upon user authentication.

`cas_server.default_settings.CAS_SQL_PASSWORD_CHECK = 'crypt'`

The method used to check the user password. Must be one of "crypt", "ldap", "hex_md5", "hex_sha1", "hex_sha224", "hex_sha256", "hex_sha384", "hex_sha512", "plain".

`cas_server.default_settings.CAS_SQL_PASSWORD_CHARSET = 'utf-8'`

charset the SQL users passwords was hash with

`cas_server.default_settings.CAS_LDAP_SERVER = 'localhost'`

Address of the LDAP server

`cas_server.default_settings.CAS_LDAP_USER = None`

LDAP user bind address, for example "cn=admin, dc=crans, dc=org" for connecting to the LDAP server.

`cas_server.default_settings.CAS_LDAP_PASSWORD = None`

LDAP connection password

`cas_server.default_settings.CAS_LDAP_BASE_DN = None`

LDAP seach base DN, for example "ou=data, dc=crans, dc=org".

`cas_server.default_settings.CAS_LDAP_USER_QUERY = '(uid=%s)'`

LDAP search filter for searching user by username. User inputed usernames are escaped using `ldap3.utils.conv.escape_bytes()`.

`cas_server.default_settings.CAS_LDAP_USERNAME_ATTR = 'uid'`

LDAP attribute used for users usernames

`cas_server.default_settings.CAS_LDAP_PASSWORD_ATTR = 'userPassword'`

LDAP attribute used for users passwords

`cas_server.default_settings.CAS_LDAP_PASSWORD_CHECK = 'ldap'`

The method used to check the user password. Must be one of "crypt", "ldap", "hex_md5", "hex_sha1", "hex_sha224", "hex_sha256", "hex_sha384", "hex_sha512", "plain", "bind".

`cas_server.default_settings.CAS_LDAP_PASSWORD_CHARSET = 'utf-8'`

charset the LDAP users passwords was hash with

`cas_server.default_settings.CAS_LDAP_ATTRS_VIEW = 0`

This parameter is only used then `CAS_LDAP_PASSWORD_CHECK` is set to "bind".

- if 0 the user attributes are retrieved by connecting to the ldap as `CAS_LDAP_USER`.
- if 1 the user attributes are retrieve then the user authenticate using the user credentials. These attributes are then cached for the session.

The default is 0.

`cas_server.default_settings.CAS_TEST_USER = 'test'`

Username of the test user.

`cas_server.default_settings.CAS_TEST_PASSWORD = 'test'`

Password of the test user.

`cas_server.default_settings.CAS_TEST_ATTRIBUTES = {'alias': ['demo1', 'demo2'], 'email':`

Attributes of the test user.

`cas_server.default_settings.CAS_ENABLE AJAX_AUTH = False`

A `bool` for activatinc the hability to fetch tickets using javascript.

`cas_server.default_settings.CAS_FEDERATE = False`

A `bool` for activating the federated mode

`cas_server.default_settings.CAS_FEDERATE_REMEMBER_TIMEOUT = 604800`

Time after witch the cookie use for "remember my identity provider" expire (one week).

`cas_server.default_settings.CAS_NEW_VERSION_HTML_WARNING = True`

A `bool` for displaying a warning on html pages then a new version of the application is availbe. Once closed by a user, it is not displayed to this user until the next new version.

`cas_server.default_settings.CAS_NEW_VERSION_EMAIL_WARNING = True`

A `bool` for sending emails to `settings.ADMINS` when a new version is available.

`cas_server.default_settings.CAS_NEW_VERSION_JSON_URL = 'https://pypi.org/pypi/django-cas-s'`

URL to the pypi json of the application. Used to retrieve the version number of the last version. You should not change it.

`cas_server.default_settings.CAS_SHOW_SERVICE_MESSAGES = True`

If the service message should be displayed on the login page

`cas_server.default_settings.CAS_INFO_MESSAGES = {'cas_explained': {'discardable': True,`

Messages displayed in a info-box on the html pages of the default templates. `CAS_INFO_MESSAGES` is a `dict` mapping message name to a message `dict`. A message `dict` has 3 keys:

- `message`: A unicode, the message to display, potentially wrapped around `ugettext_lazy`
- `discardable`: A `bool`, specify if the users can close the message info-box
- `type`: One of info, success, info, warning, danger. The type of the info-box.

`CAS_INFO_MESSAGES` contains by default one message, `cas_explained`, which explain roughly the purpose of a CAS.

`cas_server.default_settings.CAS_INFO_MESSAGES_ORDER = []`

`list` of message names. Order in which info-box messages are displayed. Let the list empty to disable messages display.

`cas_server.default_settings.CAS_REMOVE_DJANGO_SESSION_COOKIE_ON_LOGOUT = False`

`bool` If `True` Django session cookie will be removed on logout from CAS server

`cas_server.default_settings.CAS_REMOVE_DJANGO_CSRF_COOKIE_ON_LOGOUT = False`

`bool` If `True` Django csrf cookie will be removed on logout from CAS server

`cas_server.default_settings.CAS_REMOVE_DJANGO_LANGUAGE_COOKIE_ON_LOGOUT = False`

`bool` If `True` Django language cookie will be removed on logout from CAS server

class `cas_server.default_settings.SessionStore` (`session_key=None`)

Bases: `django.contrib.sessions.backends.base.SessionBase`

Implement database session store.

classmethod `get_model_class()`

model

load()

Load the session data and return a dictionary.

exists (`session_key`)

Return `True` if the given `session_key` already exists.

create()

Create a new session instance. Guaranteed to create a new object with a unique key and will have saved the result once (with empty data) before the method returns.

create_model_instance (`data`)

Return a new instance of the session model object, which represents the current session state. Intended to be used for saving the session data to the database.

save (`must_create=False`)

Save the current session data to the database. If `'must_create'` is `True`, raise a database error if the saving operation doesn't create a new entry (as opposed to possibly updating an existing entry).

delete (*session_key=None*)

Delete the session data under this key. If the key is None, use the current session key value.

classmethod clear_expired ()

Remove expired sessions from the session store.

If this operation isn't possible on a given backend, it should raise `NotImplementedError`. If it isn't necessary, because the backend has a built-in expiration mechanism, it should be a no-op.

2.2.6 cas_server.federate module

federated mode helper classes

`cas_server.federate.logger = <Logger cas_server.federate (INFO)>`
 logger facility

class `cas_server.federate.CASFederateValidateUser` (*provider, service_url, re-new=False*)

Bases: `object`

Class CAS client used to authenticate the user against a CAS provider

Parameters

- **provider** (`cas_server.models.FederatedIdentityProvider`) – The provider to use for authenticate the user.
- **service_url** (*unicode*) – The service url to transmit to the provider.

username = None

the provider returned username

attributs = {}

the provider returned attributes

federated_username = None

the provider returned username this the provider suffix appended

provider = None

the identity provider

client = None

the CAS client instance

get_login_url ()

Returns the CAS provider login url

Return type `unicode`

get_logout_url (*redirect_url=None*)

Parameters **redirect_url** (`unicode` or `NoneType`) – The url to redirect to after logout from the provider, if provided.

Returns the CAS provider logout url

Return type `unicode`

verify_ticket (*ticket*)

test *ticket* against the CAS provider, if valid, create a `FederatedUser` matching provider returned username and attributes.

Parameters **ticket** (*unicode*) – The ticket to validate against the provider CAS

Returns True if the validation succeed, else False.

Return type bool

static register_slo (*username, session_key, ticket*)

association a ticket with a (username, session_key) for processing later SLO request by creating a `cas_server.models.FederateSLO` object.

Parameters

- **username** (*unicode*) – A logged user username, with the @ component.
- **session_key** (*unicode*) – A logged user session_key matching username.
- **ticket** (*unicode*) – A ticket used to authentication username for the session session_key.

clean_sessions (*logout_request*)

process a SLO request: Search for ticket values in logout_request. For each ticket value matching a `cas_server.models.FederateSLO`, disconnect the corresponding user.

Parameters **logout_request** (*unicode*) – An XML document contening one or more Single Log Out requests.

2.2.7 cas_server.forms module

forms for the app

class `cas_server.forms.BootstrapForm` (**args, **kwargs*)

Bases: `django.forms.Form`

Form base class to use bootstrap then rendering the form fields

class `cas_server.forms.BaseLogin` (**args, **kwargs*)

Bases: `BootstrapForm`

Base form with all field possibly hidden on the login pages

service = None

The service url for which the user want a ticket

lt = None

A valid LoginTicket to prevent POST replay

renew = None

Is the service asking the authentication renewal ?

gateway = None

Url to redirect to if the authentication fail (user not authenticated or bad service)

class `cas_server.forms.WarnForm` (**args, **kwargs*)

Bases: `BaseLogin`

Form used on warn page before emitting a ticket

warned = None

True if the user has been warned of the ticket emission

class `cas_server.forms.FederateSelect` (**args, **kwargs*)

Bases: `BaseLogin`

Form used on the login page when `settings.CAS_FEDERATE` is True allowing the user to choose an identity provider.

provider = None

The providers the user can choose to be used as authentication backend

warn = None

A checkbox to ask to be warn before emitting a ticket for another service

remember = None

A checkbox to remember the user choices of *provider*

class `cas_server.forms.UserCredential(*args, **kwargs)`

Bases: *BaseLogin*

Form used on the login page to retrieve user credentials

username = None

The user username

password = None

The user password

warn = None

A checkbox to ask to be warn before emitting a ticket for another service

clean()

Validate that the submitted *username* and *password* are valid

Raises `django.forms.ValidationError` – if the *username* and *password* are not valid.

Returns The cleaned POST data

Return type `dict`

class `cas_server.forms.FederateUserCredential(*args, **kwargs)`

Bases: *UserCredential*

Form used on a auto submitted page for linking the views *FederateAuth* and *LoginView*.

On successful authentication on a provider, in the view *FederateAuth* a *FederatedUser* is created by `cas_server.federate.CASFederateValidateUser.verify_ticket()` and the user is redirected to *LoginView*. This form is then automatically filled with infos matching the created *FederatedUser* using the ticket as one time password and submitted using javascript. If javascript is not enabled, a connect button is displayed.

This stub authentication form, allow to implement the federated mode with very few modifications to the *LoginView* view.

clean()

Validate that the submitted username and password are valid using the *CASFederateAuth* auth class.

Raises `django.forms.ValidationError` – if the username and password do not correspond to a *FederatedUser*.

Returns The cleaned POST data

Return type `dict`

class `cas_server.forms.TicketForm(data=None, files=None, auto_id='id_%s', pre-fix=None, initial=None, error_class=<class 'django.forms.utils.ErrorList'>, label_suffix=None, empty_permitted=False, instance=None, use_required_attribute=None, renderer=None)`

Bases: `django.forms.ModelForm`

Form for Tickets in the admin interface

2.2.8 cas_server.models module

models for the app

`cas_server.models.python_2_unicode_compatible` (*func*)

We use Django >= 3.0 with Python >= 3.4, we don't need Python 2 compatibility.

`cas_server.models.logger` = `<Logger cas_server.models (INFO)>`
logger facility

class `cas_server.models.JsonAttributes` (**args, **kwargs*)

Bases: `django.db.models.Model`

A base class for models storing attributes as a json

class `Meta`

abstract = `False`

attributes

The attributes

class `cas_server.models.FederatedIdentityProvider` (**args, **kwargs*)

Bases: `django.db.models.Model`

An identity provider for the federated mode

suffix

Suffix append to backend CAS returned username: `returned_username @ suffix`. it must be unique.

server_url

URL to the root of the CAS server application. If login page is <https://cas.example.net/cas/login> then `server_url` should be <https://cas.example.net/cas/>

cas_protocol_version

Version of the CAS protocol to use when sending requests the the backend CAS.

verbose_name

Name for this identity provider displayed on the login page.

pos

Position of the identity provider on the login page. Identity provider are sorted using the (`pos`, `verbose_name`, `suffix`) attributes.

display

Display the provider on the login page. Beware that this do not disable the identity provider, it just hide it on the login page. User will always be able to log in using this provider by fetching `/federate/suffix`.

static `build_username_from_suffix` (*username, suffix*)

Transform backend username into federated username using `suffix`

Parameters

- **username** (*unicode*) – A CAS backend returned username
- **suffix** (*unicode*) – A suffix identifying the CAS backend

Returns The federated username: `username @ suffix`.

Return type unicode

build_username (*username*)

Transform backend username into federated username

Parameters **username** (*unicode*) – A CAS backend returned username

Returns The federated username: *username* @ *suffix*.

Return type unicode

exception DoesNotExist

exception MultipleObjectsReturned

federateduser_set

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

get_cas_protocol_version_display (*, *field=<django.db.models.fields.CharField: cas_protocol_version>*)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

class `cas_server.models.FederatedUser` (*args, **kwargs)

Bases: `JsonAttributes`

A federated user as returned by a CAS provider (username and attributes)

username

The user username returned by the CAS backend on successful ticket validation

provider

A foreign key to `FederatedIdentityProvider`

ticket

The last ticket used to authenticate *username* against *provider*

last_update

Last update timestamp. Usually, the last time *ticket* has been set.

federated_username

The federated username with a suffix for the current `FederatedUser`.

classmethod `get_from_federated_username` (*username*)

Returns A `FederatedUser` object from a federated username

Return type `FederatedUser`

classmethod `clean_old_entries` ()

remove old unused `FederatedUser`


```

exception DoesNotExist

exception MultipleObjectsReturned

get_next_by_last_update (*, field=<django.db.models.fields.DateTimeField: last_update>,
                        is_next=True, **kwargs)

get_previous_by_last_update (*, field=<django.db.models.fields.DateTimeField:
                             last_update>, is_next=False, **kwargs)

id
    A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
    executed.

objects = <django.db.models.manager.Manager object>

provider_id

class cas_server.models.FederateSLO (*args, **kwargs)
    Bases: django.db.models.Model

    An association between a CAS provider ticket and a (username, session) for processing SLO

    username
        the federated username with the @ component

    session_key
        the session key for the session username has been authenticated using ticket

    ticket
        The ticket used to authenticate username

    classmethod clean_deleted_sessions ()
        remove old FederateSLO object for which the session do not exists anymore

    exception DoesNotExist

    exception MultipleObjectsReturned

    id
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

    objects = <django.db.models.manager.Manager object>

class cas_server.models.UserAttributes (*args, **kwargs)
    Bases: JsonAttributes

    Local cache of the user attributes, used then needed

    username
        The username of the user for which we cache attributes

    classmethod clean_old_entries ()
        Remove UserAttributes for which no more User exists.

    exception DoesNotExist

    exception MultipleObjectsReturned

    id
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

    objects = <django.db.models.manager.Manager object>

```

```
class cas_server.models.User(*args, **kwargs)
    Bases: django.db.models.Model

    A user logged into the CAS

    session_key
        The session key of the current authenticated user

    username
        The username of the current authenticated user

    date
        Last time the authenticated user has do something (auth, fetch ticket, etc...)

    last_login
        last time the user logged

    delete(*args, **kwargs)
        Remove the current User. If settings.CAS_FEDERATE is True, also delete the corresponding
        FederateSLO object.

    classmethod clean_old_entries()
        Remove User objects inactive since more that SESSION_COOKIE_AGE and send corresponding SingleLogout requests.

    classmethod clean_deleted_sessions()
        Remove User objects where the corresponding session do not exists anymore.

    attributes
        Property. A fresh dict for the user attributes, using settings.CAS_AUTH_CLASS if possible, and if
        not, try to fallback to cached attributes (actually only used for ldap auth class with bind password check
        mthode).

    logout(request=None)
        Send SLO requests to all services the user is logged in.

        Parameters request (django.http.HttpRequest or NoneType) – The current
        django HttpRequest to display possible failure to the user.

    get_ticket(ticket_class, service, service_pattern, renew)
        Generate a ticket using ticket_class for the service service matching service_pattern and
        asking or not for authentication renewal with renew

        Parameters

        • ticket_class (type) – ServiceTicket or ProxyTicket or ProxyGrantingTicket.

        • service (unicode) – The service url for which we want a ticket.

        • service_pattern (ServicePattern) – The service pattern matching service.
        Beware that service must match ServicePattern.pattern and the current
        User must pass ServicePattern.check_user(). These checks are not done here
        and you must perform them before calling this method.

        • renew (bool) – Should be True if authentication has been renewed. Must be False
        otherwise.

        Returns A Ticket object.

        Return type ServiceTicket or ProxyTicket or ProxyGrantingTicket.

    get_service_url(service, service_pattern, renew)
        Return the url to which the user must be redirected to after a Service Ticket has been generated
```

Parameters

- **service** (*unicode*) – The service url for which we want a ticket.
- **service_pattern** (*ServicePattern*) – The service pattern matching *service*. Beware that *service* must match *ServicePattern.pattern* and the current *User* must pass *ServicePattern.check_user()*. These checks are not done here and you must perform them before calling this method.
- **renew** (*bool*) – Should be *True* if authentication has been renewed. Must be *False* otherwise.

Return unicode The service url with the ticket GET param added.

Return type *unicode*

exception DoesNotExist

exception MultipleObjectsReturned

get_next_by_date (*, *field*=<django.db.models.fields.DateTimeField: *date*>, *is_next*=*True*, ***kwargs*)

get_next_by_last_login (*, *field*=<django.db.models.fields.DateTimeField: *last_login*>, *is_next*=*True*, ***kwargs*)

get_previous_by_date (*, *field*=<django.db.models.fields.DateTimeField: *date*>, *is_next*=*False*, ***kwargs*)

get_previous_by_last_login (*, *field*=<django.db.models.fields.DateTimeField: *last_login*>, *is_next*=*False*, ***kwargs*)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

proxygrantingticket

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

Parent.children is a *ReverseManyToOneDescriptor* instance.

Most of the implementation is delegated to a dynamically defined manager class built by *create_forward_many_to_many_manager()* defined below.

proxyticket

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

Parent.children is a *ReverseManyToOneDescriptor* instance.

Most of the implementation is delegated to a dynamically defined manager class built by *create_forward_many_to_many_manager()* defined below.

serviceticket

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

exception cas_server.models.ServicePatternException

Bases: `exceptions.Exception`

Base exception of exceptions raised in the `ServicePattern` model

exception cas_server.models.BadUsername

Bases: `ServicePatternException`

Exception raised then an non allowed username try to get a ticket for a service

exception cas_server.models.BadFilter

Bases: `ServicePatternException`

Exception raised then a user try to get a ticket for a service and do not reach a condition

exception cas_server.models.UserFieldNotDefined

Bases: `ServicePatternException`

Exception raised then a user try to get a ticket for a service using as username an attribut not present on this user

class cas_server.models.ServicePattern(*args, **kwargs)

Bases: `django.db.models.Model`

Allowed services pattern against services are tested to

pos

service patterns are sorted using the `pos` attribute

name

A name for the service (this can bedisplayed to the user on the login page)

pattern

A regular expression matching services. “Will usually looks like ‘`^https://some.server.com/path/.*$`’. As it is a regular expression, special character must be escaped with a ‘`\`’.

user_field

Name of the attribute to transmit as username, if empty the user login is used

restrict_users

A boolean allowing to limit username allowed to connect to `usernames`.

proxy

A boolean allowing to deliver `ProxyTicket` to the service.

proxy_callback

A boolean allowing the service to be used as a proxy callback (via the `pgtUrl` GET param) to deliver `ProxyGrantingTicket`.

single_log_out

Enable `SingleLogout` for the service. Old validaed tickets for the service will be kept until `settings`.

CAS_TICKET_TIMEOUT after what a SLO request is send to the service and the ticket is purged from database. A SLO can be send earlier if the user log-out.

single_log_out_callback

An URL where the SLO request will be POST. If empty the service url will be used. This is usefull for non HTTP proxied services like smtp or imap.

check_user (*user*)

Check if user if allowed to use theses services. If user is not allowed, raises one of *BadFilter*, *UserFieldNotDefined*, *BadUsername*

Parameters *user* (*User*) – a *User* object

Raises

- *BadUsername* – if *restrict_users* if True and *User.username* is not within *usernames*.
- *BadFilter* – if a *FilterAttributValue* condition of *filters* cannot be verified.
- *UserFieldNotDefined* – if *user_field* is defined and its value is not within *User.attributes*.

Returns True

Return type bool

classmethod validate (*service*)

Get a *ServicePattern* instance from a service url.

Parameters *service* (*unicode*) – A service url

Returns A *ServicePattern* instance matching service.

Return type *ServicePattern*

Raises *ServicePattern.DoesNotExist* – if no *ServicePattern* is matching service.

exception DoesNotExist

exception MultipleObjectsReturned

attributs

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

Parent.children is a *ReverseManyToOneDescriptor* instance.

Most of the implementation is delegated to a dynamically defined manager class built by *create_forward_many_to_many_manager()* defined below.

filters

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = `<django.db.models.manager.Manager object>`

proxygrantingticket

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

proxyticket

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

replacements

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

serviceticket

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

usernames

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

```
class cas_server.models.Username(*args, **kwargs)
```

Bases: `django.db.models.Model`

A list of allowed usernames on a *ServicePattern*

value

username allowed to connect to the service

service_pattern

ForeignKey to a *ServicePattern*. *Username* instances for a *ServicePattern* are accessible through its *ServicePattern.usernames* attribute.

exception DoesNotExist**exception MultipleObjectsReturned****id**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

service_pattern_id

```
class cas_server.models.ReplaceAttributeName(*args, **kwargs)
```

Bases: `django.db.models.Model`

A replacement of an attribute name for a *ServicePattern*. It also tell to transmit an attribute of *User.attributes* to the service. An empty *replace* mean to use the original attribute name.

name

Name the attribute: a key of *User.attributes*

replace

The name of the attribute to transmit to the service. If empty, the value of *name* is used.

service_pattern

ForeignKey to a *ServicePattern*. *ReplaceAttributeName* instances for a *ServicePattern* are accessible through its *ServicePattern.attributes* attribute.

exception DoesNotExist**exception MultipleObjectsReturned****id**

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

service_pattern_id

```
class cas_server.models.FilterAttributeValue(*args, **kwargs)
    Bases: django.db.models.Model

    A filter on User.attributes for a ServicePattern. If a User do not have an attribute attribut or its
    value do not match pattern, then ServicePattern.check_user() will raises BadFilter if called
    with that user.

    attribut
        The name of a user attribute

    pattern
        A regular expression the attribute attribut value must verify. If attribut if a list, only one of the
        list values needs to match.

    service_pattern
        ForeignKey to a ServicePattern. FilterAttributeValue instances for a ServicePattern
        are accessible thought its ServicePattern.filters attribute.

    exception DoesNotExist

    exception MultipleObjectsReturned

    id
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

    objects = <django.db.models.manager.Manager object>

    service_pattern_id

class cas_server.models.ReplaceAttributeValue(*args, **kwargs)
    Bases: django.db.models.Model

    A replacement (using a regular expression) of an attribute value for a ServicePattern.

    attribut
        Name the attribute: a key of User.attributes

    pattern
        A regular expression matching the part of the attribute value that need to be changed

    replace
        The replacement to what is mached by pattern. groups are capture by \1, \2 ...

    service_pattern
        ForeignKey to a ServicePattern. ReplaceAttributeValue instances for a ServicePattern
        are accessible thought its ServicePattern.replacements attribute.

    exception DoesNotExist

    exception MultipleObjectsReturned

    id
        A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is
        executed.

    objects = <django.db.models.manager.Manager object>

    service_pattern_id

class cas_server.models.Ticket(*args, **kwargs)
    Bases: JsonAttributes

    Generic class for a Ticket
```



```

class Meta

    abstract = False

user
    ForeignKey to a User.

validate
    A boolean. True if the ticket has been validated

service
    The service url for the ticket

service_pattern
    ForeignKey to a ServicePattern. The ServicePattern corresponding to service. Use ServicePattern.validate() to find it.

creation
    Date of the ticket creation

renew
    A boolean. True if the user has just renew his authentication

single_log_out
    A boolean. Set to service_pattern attribute ServicePattern.single_log_out value.

VALIDITY = 60
    Max duration between ticket creation and its validation. Any validation attempt for the ticket after creation + VALIDITY will fail as if the ticket do not exists.

TIMEOUT = 86400
    Time we keep ticket with single_log_out set to True before sending SingleLogOut requests.

exception DoesNotExist
    raised in Ticket.get() then ticket prefix and ticket classes mismatch

static send_slos (queryset_list)
    Send SLO requests to each ticket of each queryset of queryset_list

    Parameters queryset_list (list) – A list a Ticket queryset

    Returns A list of possibly encountered Exception

    Return type list

classmethod clean_old_entries ()
    Remove old ticket and send SLO to timed-out services

logout (session, async_list=None)
    Send a SLO request to the ticket service

static get_class (ticket, classes=None)
    Return the ticket class of ticket

    Parameters

    • ticket (unicode) – A ticket

    • classes (list) – Optinal argument. A list of possible Ticket subclasses

    Returns The class corresponding to ticket (ServiceTicket or ProxyTicket or ProxyGrantingTicket) if found among classes, ``None otherwise.

    Return type type or NoneType

```

username()

The username to send on ticket validation

Returns The value of the corresponding user attribute if `service_pattern.user_field` is set, the user username otherwise.

attributs_flat()

generate attributes list for template rendering

Returns An list of (attribute name, attribute value) of all user attributes flattened (no nested list)

Return type list of tuple of unicode

classmethod get(ticket, renew=False, service=None)

Search the database for a valid ticket with provided arguments

Parameters

- **ticket** (unicode) – A ticket value
- **renew** (bool) – Is authentication renewal needed
- **service** (unicode) – Optional argument. The ticket service

Raises

- **`Ticket.DoesNotExist`** – if no class is found for the ticket prefix
- **`cls.DoesNotExist`** – if ticket value is not found in th database

Returns a `Ticket` instance

Return type `Ticket`

get_next_by_creation (*, field=<django.db.models.fields.DateTimeField: creation>, is_next=True, **kwargs)

get_previous_by_creation (*, field=<django.db.models.fields.DateTimeField: creation>, is_next=False, **kwargs)

service_pattern_id

user_id

class cas_server.models.ServiceTicket(*args, **kwargs)

Bases: `Ticket`

A Service Ticket

PREFIX = 'ST'

The ticket prefix used to differentiate it from other tickets types

value

The ticket value

exception DoesNotExist

exception MultipleObjectsReturned

get_next_by_creation (*, field=<django.db.models.fields.DateTimeField: creation>, is_next=True, **kwargs)

get_previous_by_creation (*, field=<django.db.models.fields.DateTimeField: creation>, is_next=False, **kwargs)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

service_pattern

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

Child.parent is a ForwardManyToOneDescriptor instance.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

Child.parent is a ForwardManyToOneDescriptor instance.

class cas_server.models.ProxyTicket (*args, **kwargs)

Bases: *Ticket*

A Proxy Ticket

PREFIX = 'PT'

The ticket prefix used to differentiate it from other tickets types

value

The ticket value

exception DoesNotExist

exception MultipleObjectsReturned

get_next_by_creation (*, field=<django.db.models.fields.DateTimeField: creation>, is_next=True, **kwargs)

get_previous_by_creation (*, field=<django.db.models.fields.DateTimeField: creation>, is_next=False, **kwargs)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

proxies

Accessor to the related objects manager on the reverse side of a many-to-one relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Parent.children` is a `ReverseManyToOneDescriptor` instance.

Most of the implementation is delegated to a dynamically defined manager class built by `create_forward_many_to_many_manager()` defined below.

service_pattern

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Child.parent` is a `ForwardManyToOneDescriptor` instance.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

`Child.parent` is a `ForwardManyToOneDescriptor` instance.

class `cas_server.models.ProxyGrantingTicket` (*args, **kwargs)

Bases: `Ticket`

A Proxy Granting Ticket

PREFIX = 'PGT'

The ticket prefix used to differentiate it from other tickets types

VALIDITY = 3600

ProxyGranting ticket are never validated. However, they can be used during `VALIDITY` to get `ProxyTicket` for `user`

value

The ticket value

exception DoesNotExist

exception MultipleObjectsReturned

get_next_by_creation (*, field=<django.db.models.fields.DateTimeField: creation>, is_next=True, **kwargs)

get_previous_by_creation (*, field=<django.db.models.fields.DateTimeField: creation>, is_next=False, **kwargs)

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

service_pattern

Accessor to the related object on the forward side of a many-to-one or one-to-one (via `ForwardOneToOneDescriptor` subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

Child.parent is a ForwardManyToOneDescriptor instance.

user

Accessor to the related object on the forward side of a many-to-one or one-to-one (via ForwardOneToOneDescriptor subclass) relation.

In the example:

```
class Child(Model):
    parent = ForeignKey(Parent, related_name='children')
```

Child.parent is a ForwardManyToOneDescriptor instance.

class cas_server.models.Proxy(*args, **kwargs)

Bases: django.db.models.Model

A list of proxies on *ProxyTicket*

url

Service url of the PGT used for getting the associated *ProxyTicket*

proxy_ticket

ForeignKey to a *ProxyTicket*. *Proxy* instances for a *ProxyTicket* are accessible through its *ProxyTicket.proxies* attribute.

exception DoesNotExist

exception MultipleObjectsReturned

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

proxy_ticket_id

class cas_server.models.NewVersionWarning(*args, **kwargs)

Bases: django.db.models.Model

The last new version available version sent

version

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

exception DoesNotExist

exception MultipleObjectsReturned

id

A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

objects = <django.db.models.manager.Manager object>

classmethod send_mails()

For each new django-cas-server version, if the current instance is not up to date send one mail to settings.ADMINS.

2.2.9 cas_server.urls module

urls for the app

```
cas_server.urls.re_path(route, view, kwargs=None, name=None, *, Pattern=<class
                        'django.urls.resolvers.RegexPattern'>)
```

2.2.10 cas_server.utils module

Some util function for the app

```
cas_server.utils.logger = <Logger cas_server.utils (INFO)>
    logger facility
```

```
cas_server.utils.json_encode(obj)
    Encode a python object to json
```

```
cas_server.utils.context(params)
    Function that add some variable to the context before template rendering
```

Parameters `params` (*dict*) – The context dictionary used to render templates.

Returns The `params` dictionary with the key `settings` set to `django.conf.settings`.

Return type *dict*

```
cas_server.utils.json_response(request, data)
    Wrapper dumping data to a json and sending it to the user with an HttpResponse
```

Parameters

- **request** (*django.http.HttpRequest*) – The request object used to generate this response.
- **data** (*dict*) – The python dictionary to return as a json

Returns The content of `data` serialized in json

Return type *django.http.HttpResponse*

```
cas_server.utils.import_attr(path)
    transform a python dotted path to the attr
```

Parameters `path` (*unicode* or *str* or anything) – A dotted path to a python object or a python object

Returns The python object pointed by the dotted path or the python object unchanged

```
cas_server.utils.redirect_params(url_name, params=None)
    Redirect to url_name with params as querystring
```

Parameters

- **url_name** (*unicode*) – a URL pattern name
- **params** (*dict* or *NoneType*) – Some parameter to append to the reversed URL

Returns A redirection to the URL with name `url_name` with `params` as querystring.

Return type *django.http.HttpResponseRedirect*

```
cas_server.utils.reverse_params(url_name, params=None, **kwargs)
    compute the reverse url of url_name and add to it parameters from params as querystring
```

Parameters

- **url_name** (*unicode*) – a URL pattern name
- **params** (*dict* or *NoneType*) – Some parameter to append to the reversed URL
- ****kwargs** – additional parameters needed to compute the reverse URL

Returns The computed reverse URL of `url_name` with possible querystring from `params`

Return type *unicode*

`cas_server.utils.copy_params (get_or_post_params, ignore=None)`
 copy a `django.http.QueryDict` in a `dict` ignoring keys in the set `ignore`

Parameters

- **get_or_post_params** (*django.http.QueryDict*) – A GET or POST `QueryDict`
- **ignore** (*set*) – An optional set of keys to ignore during the copy

Returns A copy of `get_or_post_params`

Return type *dict*

`cas_server.utils.set_cookie (response, key, value, max_age)`
 Set the cookie key on response with value value valid for max_age secondes

Parameters

- **response** (*django.http.HttpResponse*) – a django response where to set the cookie
- **key** (*unicode*) – the cookie key
- **value** (*unicode*) – the cookie value
- **max_age** (*int*) – the maximum validity age of the cookie

`cas_server.utils.get_current_url (request, ignore_params=None)`
 Giving a django request, return the current http url, possibly ignoring some GET parameters

Parameters

- **request** (*django.http.HttpRequest*) – The current request object.
- **ignore_params** (*set*) – An optional set of GET parameters to ignore

Returns The URL of the current page, possibly omitting some parameters from `ignore_params` in the querystring.

Return type *unicode*

`cas_server.utils.update_url (url, params)`
 update parameters using params in the url query string

Parameters

- **url** (*unicode* or *str*) – An URL possibly with a querystring
- **params** (*dict*) – A dictionary of parameters for updating the url querystring

Returns The URL with an updated querystring

Return type *unicode*

`cas_server.utils.unpack_nested_exception (error)`
 If exception are stacked, return the first one

Parameters **error** – A python exception with possible exception embeded within

Returns A python exception with no exception embeded within

`cas_server.utils.gen_lt()`

Generate a Login Ticket

Returns A ticket with prefix `settings.CAS_LOGIN_TICKET_PREFIX` and length `settings.CAS_LT_LEN`

Return type unicode

`cas_server.utils.gen_st()`

Generate a Service Ticket

Returns A ticket with prefix `settings.CAS_SERVICE_TICKET_PREFIX` and length `settings.CAS_ST_LEN`

Return type unicode

`cas_server.utils.gen_pt()`

Generate a Proxy Ticket

Returns A ticket with prefix `settings.CAS_PROXY_TICKET_PREFIX` and length `settings.CAS_PT_LEN`

Return type unicode

`cas_server.utils.gen_pgt()`

Generate a Proxy Granting Ticket

Returns A ticket with prefix `settings.CAS_PROXY_GRANTING_TICKET_PREFIX` and length `settings.CAS_PGT_LEN`

Return type unicode

`cas_server.utils.gen_pgtiou()`

Generate a Proxy Granting Ticket IOU

Returns A ticket with prefix `settings.CAS_PROXY_GRANTING_TICKET_IOU_PREFIX` and length `settings.CAS_PGTIOU_LEN`

Return type unicode

`cas_server.utils.gen_saml_id()`

Generate an saml id

Returns A random id of length `settings.CAS_TICKET_LEN`

Return type unicode

`cas_server.utils.get_tuple(nuplet, index, default=None)`

Parameters

- **nuplet** (*tuple*) – A tuple
- **index** (*int*) – An index
- **default** – An optional default value

Returns `nuplet[index]` if defined, else default (possibly None)

`cas_server.utils.crypt_salt_is_valid(salt)`

Validate a salt as crypt salt

Parameters **salt** (*str*) – a password salt

Returns True if salt is a valid crypt salt on this system, False otherwise

Return type `bool`

class `cas_server.utils.LdapHashUserPassword`

Bases: `object`

Class to deal with hashed password as defined at <https://tools.ietf.org/id/draft-stroeder-hashed-userpassword-values-01.html>

schemes_salt = `{b'{CRYPT}', b'{SMD5}', b'{SSHA256}', b'{SSHA384}', b'{SSHA512}', b'{SS`
 valide schemes that require a salt

schemes_nosalt = `{b'{MD5}', b'{SHA256}', b'{SHA384}', b'{SHA512}', b'{SHA}'}`
 valide sschemes that require no slat

exception `BadScheme`

Bases: `ValueError`

Error raised then the hash scheme is not in `LdapHashUserPassword.schemes_salt` + `LdapHashUserPassword.schemes_nosalt`

exception `BadHash`

Bases: `ValueError`

Error raised then the hash is too short

exception `BadSalt`

Bases: `ValueError`

Error raised then, with the scheme `{CRYPT}`, the salt is invalid

classmethod `hash(scheme, password, salt=None, charset='utf8')`

Hash password with scheme using salt. This three variable beeing encoded in charset.

Parameters

- **scheme** (*bytes*) – A valid scheme
- **password** (*bytes*) – A byte string to hash using scheme
- **salt** (*bytes*) – An optional salt to use if scheme requires any
- **charset** (*str*) – The encoding of scheme, password and salt

Returns The hashed password encoded with charset

Return type `bytes`

classmethod `get_scheme(hashed_passord)`

Return the scheme of hashed_passord or raise `BadHash`

Parameters **hashed_passord** (*bytes*) – A hashed password

Returns The scheme used by the hashed password

Return type `bytes`

Raises `BadHash` – if no valid scheme is found within hashed_passord

classmethod `get_salt(hashed_passord)`

Return the salt of hashed_passord possibly empty

Parameters **hashed_passord** (*bytes*) – A hashed password

Returns The salt used by the hashed password (empty if no salt is used)

Return type `bytes`

Raises **BadHash** – if no valid scheme is found within `hashed_password` or if the hashed password is too short for the scheme found.

`cas_server.utils.check_password(method, password, hashed_password, charset)`

Check that password match `hashed_password` using `method`, assuming the encoding is `charset`.

Parameters

- **method** (*str*) – one of "crypt", "ldap", "hex_md5", "hex_sha1", "hex_sha224", "hex_sha256", "hex_sha384", "hex_sha512", "plain"
- **password** (*str* or *unicode*) – The user inputted password
- **hashed_password** (*str* or *unicode*) – The hashed password as stored in the database
- **charset** (*str*) – The used char encoding (also used internally, so it must be valid for the charset used by password when it was initially)

Returns True if password match `hashed_password` using `method`, False otherwise

Return type *bool*

`cas_server.utils.decode_version(version)`

decode a version string following version semantic <http://semver.org/> input a tuple of int. It will work as long as we do not use pre release versions.

Parameters **version** (*unicode*) – A dotted version

Returns A tuple a int

Return type *tuple*

`cas_server.utils.last_version()`

Fetch the last version from pypi and return it. On successful fetch from pypi, the response is cached 24h, on error, it is cached 10 min.

Returns the last django-cas-server version

Return type *unicode*

`cas_server.utils.dictfetchall(cursor)`

Return all rows from a django cursor as a dict

`cas_server.utils.logout_request(ticket)`

Forge a SLO logout request

Parameters **ticket** (*unicode*) – A ticket value

Returns A SLO XML body request

Return type *unicode*

`cas_server.utils.regex_validator(value)`

Test that `value` is a valid regular expression

Parameters **value** (*unicode*) – A regular expression to test

Raises **ValidationError** – if `value` is not a valid regular expression

2.2.11 cas_server.views module

views for the app

`cas_server.views.python_2_unicode_compatible(func)`

We use Django >= 3.0 with Python >= 3.4, we don't need Python 2 compatibility.

```

class cas_server.views.LogoutMixin
    Bases: object
    destroy CAS session utils
    logout (all_session=False)
        effectively destroy a CAS session

        Parameters all_session (boolean) – If True destroy all the user sessions, otherwise
            destroy the current user session.

        Returns The number of destroyed sessions

        Return type int

class cas_server.views.CsrfExemptView (**kwargs)
    Bases: django.views.generic.base.View
    base class for csrf exempt class views
    dispatch (request, *args, **kwargs)
        dispatch different http request to the methods of the same name

        Parameters request (django.http.HttpRequest) – The current request object

class cas_server.views.LogoutView (**kwargs)
    Bases: django.views.generic.base.View, cas_server.views.LogoutMixin
    destroy CAS session (logout) view

    request = None
        current django.http.HttpRequest object

    service = None
        service GET parameter

    url = None
        url GET paramet

    ajax = None
        True if the HTTP_X_AJAX http header is sent and settings.CAS_ENABLE_AJAX_AUTH is True,
        False otherwise.

    init_get (request)
        Initialize the LogoutView attributes on GET request

        Parameters request (django.http.HttpRequest) – The current request object

    static delete_cookies (response)

    get (request, *args, **kwargs)
        method called on GET request on this view

        Parameters request (django.http.HttpRequest) – The current request object

class cas_server.views.FederateAuth (**kwargs)
    Bases: cas_server.views.CsrfExemptView
    view to authenticated user against a backend CAS then CAS_FEDERATE is True
    csrf is disabled for allowing SLO requests reception.

    service_url = None
        current URL used as service URL by the CAS client

```

get_cas_client (*request, provider, renew=False*)
 return a CAS client object matching provider

Parameters

- **request** (*django.http.HttpRequest*) – The current request object
- **provider** (*cas_server.models.FederatedIdentityProvider*) – the user identity provider

Returns The user CAS client object

Return type *federate.CASFederateValidateUser*

post (*request, provider=None, *args, **kwargs*)
 method called on POST request

Parameters

- **request** (*django.http.HttpRequest*) – The current request object
- **provider** (*unicode*) – Optional parameter. The user provider suffix.

get (*request, provider=None*)
 method called on GET request

Parameters

- **request** (*django.http.HttpRequest**self.*) – The current request object
- **provider** (*unicode*) – Optional parameter. The user provider suffix.

class *cas_server.views.LoginView* (***kwargs*)
 Bases: *django.views.generic.base.View*, *cas_server.views.LogoutMixin*
 credential requestor / acceptor

user = **None**
 The current *models.User* object

form = **None**
 The form to display to the user

request = **None**
 current *django.http.HttpRequest* object

service = **None**
 service GET/POST parameter

renew = **None**
 True if renew GET/POST parameter is present and not “False”

warn = **None**
 the warn GET/POST parameter

gateway = **None**
 the gateway GET/POST parameter

method = **None**
 the method GET/POST parameter

ajax = **None**
 True if the HTTP_X AJAX http header is sent and *settings.CAS_ENABLE_AJAX_AUTH* is True,
 False otherwise.

renewed = False

True if the user has just authenticated

warned = False

True if renew GET/POST parameter is present and not “False”

username = None

The *FederateAuth* transmited username (only used if `settings.CAS_FEDERATE` is True)

ticket = None

The *FederateAuth* transmited ticket (only used if `settings.CAS_FEDERATE` is True)

INVALID_LOGIN_TICKET = 1

USER_LOGIN_OK = 2

USER_LOGIN_FAILURE = 3

USER_ALREADY_LOGGED = 4

USER_AUTHENTICATED = 5

USER_NOT_AUTHENTICATED = 6

init_post (*request*)

Initialize POST received parameters

Parameters **request** (*django.http.HttpRequest*) – The current request object

gen_lt ()

Generate a new LoginTicket and add it to the list of valid LT for the user

check_lt ()

Check is the POSTed LoginTicket is valid, if yes invalide it

Returns True if the LoginTicket is valid, False otherwise

Return type *bool*

post (*request*, **args*, ***kwargs*)

method called on POST request on this view

Parameters **request** (*django.http.HttpRequest*) – The current request object

process_post ()

Analyse the POST request:

- check that the LoginTicket is valid
- check that the user sumited credentials are valid

Returns

- *INVALID_LOGIN_TICKET* if the POSTed LoginTicket is not valid
- *USER_ALREADY_LOGGED* if the user is already logged and do no request reauthentication.
- *USER_LOGIN_FAILURE* if the user is not logged or request for reauthentication and his credentials are not valid
- *USER_LOGIN_OK* if the user is not logged or request for reauthentication and his credentials are valid

Return type *int*

init_get (*request*)

Initialize GET received parameters

Parameters **request** (*django.http.HttpRequest*) – The current request object

get (*request, *args, **kwargs*)

method called on GET request on this view

Parameters **request** (*django.http.HttpRequest*) – The current request object

process_get ()

Analyse the GET request

Returns

- *USER_NOT_AUTHENTICATED* if the user is not authenticated or is requesting for authentication renewal
- *USER_AUTHENTICATED* if the user is authenticated and is not requesting for authentication renewal

Return type *int*

init_form (*values=None*)

Initialization of the good form depending of POST and GET parameters

Parameters **values** (*django.http.QueryDict*) – A POST or GET QueryDict

service_login ()

Perform login against a service

Returns

- The rendering of the *settings.CAS_WARN_TEMPLATE* if the user asked to be warned before ticket emission and has not yep been warned.
- The redirection to the service URL with a ticket GET parameter
- The redirection to the service URL without a ticket if ticket generation failed and the *gateway* attribute is set
- The rendering of the *settings.CAS_LOGGED_TEMPLATE* template with some error messages if the ticket generation failed (e.g: user not allowed).

Return type *django.http.HttpResponse*

authenticated ()

Processing authenticated users

Returns

- The returned value of *service_login()* if *service* is defined
- The rendering of *settings.CAS_LOGGED_TEMPLATE* otherwise

Return type *django.http.HttpResponse*

not_authenticated ()

Processing non authenticated users

Returns

- The rendering of *settings.CAS_LOGIN_TEMPLATE* with various messages depending of GET/POST parameters
- The redirection to *FederateAuth* if *settings.CAS_FEDERATE* is True and the “remember my identity provider” cookie is found

Return type `django.http.HttpResponse`

common()

Common part execute upon GET and POST request

Returns

- The returned value of `authenticated()` if the user is authenticated and not requesting for authentication or if the authentication has just been renewed
- The returned value of `not_authenticated()` otherwise

Return type `django.http.HttpResponse`

class `cas_server.views.Auth(**kwargs)`

Bases: `cas_server.views.CsrfExemptView`

A simple view to validate username/password/service tuple

csrf is disable as it is intended to be used by programs. Security is assured by a shared secret between the programs dans django-cas-server.

static post (*request*)

method called on POST request on this view

Parameters **request** (`django.http.HttpRequest`) – The current request object

Returns `HttpResponse(u"yes\n")` if the POSTed tuple (username, password, service) if valid (i.e. (username, password) is valid dans username is allowed on service). `HttpResponse(u"no\n...")` otherwise, with possibly an error message on the second line.

Return type `django.http.HttpResponse`

class `cas_server.views.Validate(**kwargs)`

Bases: `django.views.generic.base.View`

service ticket validation

static get (*request*)

method called on GET request on this view

Parameters **request** (`django.http.HttpRequest`) – The current request object

Returns

- `HttpResponse("yes\nusername")` if submitted (service, ticket) is valid
- else `HttpResponse("no\n")`

Return type `django.http.HttpResponse`

exception `cas_server.views.ValidationBaseError` (*code*, *msg*="")

Bases: `Exception`

Base class for both saml and cas validation error

code = `None`

The error code

msg = `None`

The error message

render (*request*)

render the error template for the exception

Parameters **request** (`django.http.HttpRequest`) – The current request object:

Returns the rendered `cas_server/serviceValidateError.xml` template

Return type `django.http.HttpResponse`

exception `cas_server.views.ValidateError` (*code*, *msg*=")

Bases: `cas_server.views.ValidationBaseError`

handle service validation error

template = `'cas_server/serviceValidateError.xml'`

template to be render for the error

context ()

content to use to render *template*

Returns A dictionary to contextualize *template*

Return type `dict`

class `cas_server.views.ValidateService` (***kwargs*)

Bases: `django.views.generic.base.View`

service ticket validation [CAS 2.0] and [CAS 3.0]

request = `None`

Current `django.http.HttpRequest` object

service = `None`

The service GET parameter

ticket = `None`

the ticket GET parameter

pgt_url = `None`

the pgtUrl GET parameter

renew = `None`

the renew GET parameter

allow_proxy_ticket = `False`

specify if ProxyTicket are allowed by the view. Hence we user the same view for `/serviceValidate` and `/proxyValidate` just changing the parameter.

get (*request*)

method called on GET request on this view

Parameters **request** (`django.http.HttpRequest`) – The current request object:

Returns The rendering of `cas_server/serviceValidate.xml` if no errors is raised, the rendering of `cas_server/serviceValidateError.xml` otherwise.

Return type `django.http.HttpResponse`

process_ticket ()

fetch the ticket against the database and check its validity

Raises `ValidateError` – if the ticket is not found or not valid, potentially for that service

Returns A couple (ticket, proxies list)

Return type `tuple`

process_pgturl (*params*)

Handle PGT request

Parameters **params** (`dict`) – A template context dict

Raises *ValidateError* – if pgUrl is invalid or if TLS validation of the pgUrl fails

Returns The rendering of `cas_server/serviceValidate.xml`, using `params`

Return type `django.http.HttpResponse`

```
class cas_server.views.Proxy(**kwargs)
    Bases: django.views.generic.base.View
    proxy ticket service

    request = None
        Current django.http.HttpRequest object

    pgt = None
        A ProxyGrantingTicket from the pg GET parameter

    target_service = None
        the targetService GET parameter

    get(request)
        method called on GET request on this view

        Parameters request (django.http.HttpRequest) – The current request object:

        Returns The returned value of process_proxy() if no error is raised, else the rendering of
            cas_server/serviceValidateError.xml.

        Return type django.http.HttpResponse

    process_proxy()
        handle PT request

        Raises ValidateError – if the PGT is not found, or the target service not allowed or the
            user not allowed on the target service.

        Returns The rendering of cas_server/proxy.xml

        Return type django.http.HttpResponse

exception cas_server.views.SamlValidateError(code, msg="")
    Bases: cas_server.views.ValidationBaseError
    handle saml validation error

    template = 'cas_server/samlValidateError.xml'
        template to be render for the error

    context()

        Returns A dictionary to contextualize template

        Return type dict

class cas_server.views.SamlValidate(**kwargs)
    Bases: cas_server.views.CsrfExemptView
    SAML ticket validation

    request = None

    target = None

    ticket = None

    root = None
```

post (*request*, *args, **kwargs)

method called on POST request on this view

Parameters **request** (*django.http.HttpRequest*) – The current request object

Returns the rendering of `cas_server/samlValidate.xml` if no error is raised, else the rendering of `cas_server/samlValidateError.xml`.

Return type *django.http.HttpResponse*

process_ticket ()

validate ticket from SAML XML body

Raises `SamlValidateError`: if the ticket is not found or not valid, or if we fail to parse the posted XML.

Returns a ticket object

Return type *models.Ticket*

2.3 Module contents

A django CAS server application

`cas_server.VERSION = '2.0.0'`

version of the application

CHAPTER 3

Change Log

All notable changes to this project will be documented in this file.

Table of Contents

- *Change Log*
 - *Unreleased*
 - *v2.0.0 - 2022-10-17*
 - *v1.3.1 - 2021-07-03*
 - *v1.3.0 - 2021-06-19*
 - *v1.2.0 - 2020-07-05*
 - *v1.1.0 - 2019-03-02*
 - *v1.0.0 - 2019-01-12*
 - *v0.9.0 - 2017-11-17*
 - *v0.8.0 - 2017-03-08*
 - *v0.7.4 - 2016-09-07*
 - *v0.7.3 - 2016-09-07*
 - *v0.7.2 - 2016-08-31*
 - *v0.7.1 - 2016-08-24*
 - *v0.7.0 - 2016-08-24*
 - *v0.6.4 - 2016-08-14*
 - *v0.6.3 - 2016-08-14*
 - *v0.6.2 - 2016-08-02*

- *v0.6.1 - 2016-07-27*
- *v0.6.0 - 2016-07-06*
- *v0.5.0 - 2016-07-01*
- *v0.4.4 - 2016-04-30*
- *v0.4.3 - 2016-03-18*
- *v0.4.2 - 2016-03-18*
- *v0.4.1 - 2015-12-23*
- *v0.4.0 - 2015-12-15*
- *v0.3.5 - 2015-12-12*
- *v0.3.4 - 2015-12-12*
- *v0.3.3 - 2015-12-12*
- *v0.3.2 - 2015-12-12 [YANKED]*
- *v0.3.1 - 2015-12-12*
- *v0.3.0 - 2015-12-12*
- *v0.2.1 - 2015-12-12*
- *v0.2.0 - 2015-12-12 [YANKED]*
- *v0.1.0 - 2015-05-22 [YANKED]*

3.1 Unreleased

3.1.1 Added

- Support for Django 4.2

3.2 v2.0.0 - 2022-10-17

3.2.1 Added

- Support for Django 4.0 and 4.1
- Add locale for zh_Hans
- Add a unit test with a non ascii char in service url
- Add settings to allow deletings Django cookies upon logout

3.2.2 Changed

- Update CI: require pytest >= 7 and remove pytest-pythonpath dependancy

3.2.3 Fixes

- Fix unicode sandwich issue in `cas_server.utils.update_url`
- Fix `DeprecationWarning` about `default_app_config` in Django 3.2
- Fix `DeprecationWarning` about `USE_L10N` in Django 4.0

3.2.4 Removed

- Drop support for python 2.7 (now deprecated for more than 2 years, expect it to break now or in a near future)
- Drop support for python 3.5 (but it should keep working for a while. `pytest >= 7` do not support python 3.5 and Debian Stretch support ended)

3.3 v1.3.1 - 2021-07-03

3.3.1 Fixes

- Documentation generation to works with latest Django and sphinx version
- Update classifier and dependencies versions in `setup.py`

3.4 v1.3.0 - 2021-06-19

3.4.1 Added

- Support for Django 3.1 and 3.2
- Implement `CAS_LDAP_ATTRS_VIEW` set to 0: then using ldap bind mode, user attributes can be retrieve either using `CAS_LDAP_USER` or using the binded user credentials.
- Added ppc64le architecture support on travis-ci (django-cas-server is included in the ppc64le versions of RHEL and Ubuntu)
- Python 3.9 support

3.4.2 Fixes

- Allow to use user attributes if auth by ldap bind
- Fix spelling mistakes in french translation
- Fix bug model datefield Form (Federated User Admin)
- `django.conf.urls` is deprecated and will be removed in Django 4.0. Use `django.urls.re_path` instead

3.4.3 Removed

- Drop support for Django 3.0 as it reached end of life.

3.5 v1.2.0 - 2020-07-05

3.5.1 Added

- Bootstrap 4 templates
- Support for Django 2.2 and 3.0

3.5.2 Fixes

- Replace calls to `add_description_unit`. As of Sphinx 2.4, the deprecated `add_description_unit` function has been removed.
- Fix CRYPT-DES hash method for LDAP
- Fix various spelling mistakes in README.rst
- Service URL: keep blank GET arguments

3.5.3 Changed

- Use python3 for flake8, check_rst and coverage
- Update README.rst quickstart for using python3 by default

3.5.4 Removed

- Drop support for Django 2.0 and 2.1 as it reached end of life. We still keep Django 1.11 as it is the last supported release by python2 AND the currently packaged version of Django in Debian Buster (current stable).

3.6 v1.1.0 - 2019-03-02

3.6.1 Added

- Support for Django 2.1

3.6.2 Fixes

- Checkbox position on the login page
- Set ldap3 client_strategy from sync to sync-restartable
- Deprecation warning for `{% load staticfiles %}` and `django.contrib.staticfiles`

3.7 v1.0.0 - 2019-01-12

3.7.1 Added

- Support for python 3.6 and Django 1.11

- Support for Django 2.0
- Keep query string then redirecting from / to /login

3.7.2 Fixes

- Add missing attributes authenticationDate, longTermAuthenticationRequestTokenUsed and isFromNewLogin from service validation response
- Catch error from calling django.contrib.staticfiles.templatetags.staticfiles.static in non-debug mode before collectstatic in cas_server.default_settings.py
- Invalid escape sequence in regular expression

3.7.3 Deprecated

- Support for Django <1.11 is dropped, it should still works for this version. Next versions will most probably be not compatible with Django <1.11
- Support for python 3.4 is dropped, it should still works for this version. Next versions may or may not works with python 3.4.

3.7.4 Other

- Migrations have been squashed for Django 2.0 support. Be sur to apply all migration before updating to this version
- Update PyPi url from <https://pypi.python.org> to <https://pypi.org>

3.8 v0.9.0 - 2017-11-17

3.8.1 Added

- Dutch translation
- Protuguese translation (brazilian variant)
- Support for ldap3 version 2 or more (changes in the API) All exception are now in ldap3.core.exceptions, methodes for fetching attritutes and dn are renamed.
- Possibility to disable service message boxes on the login pages

3.8.2 Fixed

- Then using the LDAP auth backend with bind method for password check, do not try to bind if the user dn was not found. This was causing the exception 'NoneType' object has no attribute 'getitem' describe in #21
- Increase the max size of usernames (30 chars to 250)
- Fix XSS js injection

3.9 v0.8.0 - 2017-03-08

3.9.1 Added

- Add a test for login with missing parameter (username or password or both)
- Add ldap auth using bind method (use the user credentials to bind the the ldap server and let the server check the credentials)
- Add CAS_TGT_VALIDITY parameter: Max time after with the user MUST reauthenticate.

3.9.2 Fixed

- Allow both unicode and bytes dotted string in utils.import_attr
- Fix some spelling and grammar on log messages. (thanks to Allie Micka)
- Fix froms css class error on success/error due to a scpaless block
- Disable pip cache then installing with make install

3.9.3 Changed

- Update french translation

3.10 v0.7.4 - 2016-09-07

3.10.1 Fixed

- Add templatetags to Pypi package

3.11 v0.7.3 - 2016-09-07

3.11.1 Added

- Add autofocus to the username input on the login page

3.11.2 Fixed

- Really pick the last version on Pypi for new version checking. We were only sorting version string lexicographically and it would have break when we reach version 0.10.N or 0.N.10
- Only check for valid username/password if username and password POST fields are posted. This fix a bug where posting without it raise a exception are None where passed for username/password verification.

3.12 v0.7.2 - 2016-08-31

3.12.1 Added

- Add Django 1.10 support
- Add support of gitlab continuous integration

3.12.2 Fixed

- Fix BootstrapForm: placeholder on Input and Textarea only, use class form-control on Input, Select and Textarea.
- Fix lang attribute in django 1.7. On html pages, the lang attribute of the <html> was not present in django 1.7. We use now a methode to display it that is also available in django 1.7

3.13 v0.7.1 - 2016-08-24

3.13.1 Added

- Add a forgotten migration (only change help_text and validators)

3.14 v0.7.0 - 2016-08-24

3.14.1 Added

- Add a CHANGELOG.rst file.
- Add a validator to models CharField that should be regular expressions checking that user input are valids regular expressions.
- Add a CAS_INFO_MESSAGES and CAS_INFO_MESSAGES_ORDER settings allowing to display messages in info-boxes on the html pages of the default templates.

3.14.2 Changed

- Allow the user defined CAS_COMPONENT_URLS to omit not changed values.
- replace code-block without language indication by literal blocks.
- Update french translation

3.14.3 Fixed

- Some README.rst typos.
- some english typos

3.15 v0.6.4 - 2016-08-14

commit: 282e3a831b3c0b0818881c2f16d056850d572b89

3.15.1 Added

- Add a forgotten migration (only change help_text)

3.16 v0.6.3 - 2016-08-14

commit: 07a537b403c5c5e39a4ddd084f90e3a4de88a54e

3.16.1 Added

- Add powered by footer
- Add a github version badge
- documents templatetags

3.16.2 Changed

- Usage of the documented API for models _meta in auth.DjangoAuthUser
- set warn cookie using javascript if possible
- Unfold many to many attributes in auth.DjangoAuthUser attributes

3.16.3 Fixed

- typos in README.rst
- w3c validation

3.16.4 Cleaned

- Code factorisation (models.py, views.py)

3.17 v0.6.2 - 2016-08-02

commit: 773707e6c3c3fa20f697c946e31cafc591e8fee8

3.17.1 Added

- Support authentication renewal in federate mode
- Add new version email and info box then new version is available
- Add SqlAuthUser and LdapAuthUser auth classes. Deprecate the usage of MysqlAuthUser in favor of SqlAuthUser.
- Add pytest-warning to tests
- Add a checkbox to forget the identity provider if we checked “remember the identity provider”
- Add dependancies correspondance between python pypi, debian and centos packages in README

3.17.2 Changed

- Move coverage computation last in travis
- Enable logging to stderr then running tests
- Remember “warn me before...” using a cookie
- Put favicon (shortcut icon) URL in settings

3.17.3 Deprecated

- The auth class MysqlAuthUser is deprecated in favor of the SqlAuthUser class.

3.17.4 Fixed

- Use custom templatetags instead settings custom attributes to Boundfields (As it do not work with django 1.7)
- Display an error message on bad response from identity provider in federate mode instead of crashing. (e.g. Bad XML document)
- Catch base64 decode error on b64decode to raise our custom exception BadHash
- Add secret as sensitive variables/post parameter for /auth
- Only set “remember my provider” in federated mode upon successful authentication
- Since we drop django-bootstrap3 dependancies, Django default minimal version is 1.7.1
- [cas.py] Append renew=true when validating tickets

3.17.5 Cleaned

- code factorization (cas.py, forms.py)

3.18 v0.6.1 - 2016-07-27

commit: b168e0a6423c53de31aae6c444fa1d1c5083afa6

3.18.1 Added

- Add sphinx docs + autodoc
- Add the possibility to run tests with “setup.py test”
- Include docs, Makefile, coverage config and tests config to source package
- Add serviceValidate ProxyTicket tests
- Add python 3.5 tox/travis tests

3.18.2 Changed

- Use <https://badges.genua.fr> for badges

3.18.3 Fixed

- Keep LoginTicket list upon fail authentication (It prevent the next login attempts to fail because of bad LT)

3.18.4 Cleaned

- Compact federated mode migration
- Reformat default_settings.py for documentation using sphinx autodoc
- Factorize some code (from views.py to Ticket models class methods)
- Update urlpattern for django 1.10
- Drop dependancies django-picklefield and django-bootstrap3

3.19 v0.6.0 - 2016-07-06

commit: 4ad4d13baa4236c5cd72cc5216d7ff08dd361476

3.19.1 Added

- Add a section describing service patterns options to README.rst
- Add a federation mode: When the settings CAS_FEDERATE is True, django-cas-server will offer to the user to choose its CAS backend to authenticate. Hence the login page do not display anymore a username/password form but a select form with configured CASs backend. This allow to give access to CAS supported applications to users from multiple organization seamlessly.

It was originally developped to mach the need of <https://ares.fr> (Federated CAS at <https://cas.ares.fr>, example of an application using it as <https://chat.myares.fr>)

3.19.2 Fixed

- Then a ticket was marked as obtained with the user entering its credentials (aka not by SSO), and the service did not require it, ticket validation was failing. Now, if the service do not require authentication to be renewed, both ticket with renewed authentication and non renewed authentication validate successfully.

3.20 v0.5.0 - 2016-07-01

commit: e3ab64271b718a17e4cbbbabda0a2453107a83df

3.20.1 Added

- Add more password scheme support to the mysql authentication backend: ldap user attribute scheme encoding and simple password hash in hexa for md5, sha1, sha224, sha256, sha384, sha512.
- Add a main heading to template “Central Authentication Service” with a logo controlled by CAS_LOGO_URL
- Add logos to the project (svg, png)
- Add coverage computation
- link project to codacy
- Update doc: add debian requirement, correct typos, correct links

3.20.2 Changed

- Use settings to set tests username password and attributes
- Tweak the css and html for small screens
- Update travis cache for faster build
- clean Makefile, use pip to install, add target for tests

3.20.3 Fixed

- Fix “warn me”: we generate the ticket after the user agree to be connected to the service. we were generating first and the connect button was a link to the service url with the ?ticket= this could lead to situation where the ticket validity expire if the user is slow to click the connect button.
- **Fix authentication renewal: the renew parameter were not transmited when POST the login request**
and self.renew (aks for auth renewal) was use instead of self.renewed (auth was renewed) when generating a ticket.
- Fix attribute value replacement when generating a ticket: we were using the ‘name’ attribute instead of the ‘attribut’ attribut on ReplaceAttributValue
- Fix attribute value replacement when generating a ticket then the value is a list: iterate over each element of the list.
- Fix a NameError in utils.import_attr
- Fix serviceValidate and samlValidate when user_field is an attribute that is a list: we use the first element of the list as username. we were serializing the list before that.
- Correct typos

3.20.4 Cleaned

- Clean some useless conditional branches found with coverage
- Clean cas.js: use compact object declararion

- Use six for python{2|3} compatibility
- Move all unit tests to cas_server.tests and use django primitive. We also have a 100% tests coverage now. Using the django classes for tests, we do not need to use our own dirty mock.
- Move mysql backend password check to a function in utils

3.21 v0.4.4 - 2016-04-30

commit: 77d1607b0beefe8b171adcd8e2dcd974e3cdc72a

3.21.1 Added

- Add sensitive_post_parameters and sensitive_variables for passwords, so passwords are anonymised before django send an error report.

3.21.2 Fixed

- Before commit 77fc5b5 the User model had a foreign key to the Session model. After the commit, Only the session_key is store, allowing to use different backend than the Session SQL backend. So the first migration (which is 21 migrations combined) was creating the User model with the foreign key, then delete it and add the field session_key. Somehow, MySQL did not like it. Now the first migration directly create the User model with the session_key and without the foreign key to the Session SQL backend.
- Evaluate attributes variables in the template samlValidate.xml. the {{ }} was missing causing the variable name to be dispalyed instead of the variable content.
- Return username in CAS 1.0 on the second ligne of the CAS response as specified.

3.21.3 Changed

- Update tests

3.22 v0.4.3 - 2016-03-18

commit: f6d436acb49f8d32b5457c316c18c4892accfd3b

3.22.1 Fixed

- Currently, one of our dependancy, django-bootstrap3, do not support django 1.7 in its last version. So there is some detection of the current django installed version in setup.py to pin django-bootstrap3 to a version supported by django 1.7 if django 1.7 is installed, or to require at least django 1.8. The detection did not handle the case where django was not installed.
- [PEP8] Put line breaks after binary operator and not before.

3.23 v0.4.2 - 2016-03-18

commit: d1cd17d6103281b03a8c57013671057eab80d21c

3.23.1 Added

- On logout, display the number of sessions we are logged out from.

3.23.2 Fixed

- One of our dependancy, django-bootstrap3, do not support django 1.7 in its last version. Some django version detection is added to setup.py to handle that.
- Some typos
- Make errors returned by utils.import_attr clearer (as they are likely to be displayed to the django admin)

3.24 v0.4.1 - 2015-12-23

commit: 5e63f39f9b7c678a300ad2f8132166be34d1d35b

3.24.1 Added

- Add a run_test_server target to make file. Running make run_test_server will build a virtualenv, create a django projet with django-cas-server and lauch ./management.py runserver. It is quite handy to test developement version.
- Add verbose name for cas_server app and models
- Add Makefile clean targets for tox tests and test virtualenv.
- Add link on license badge to the GPLv3

3.24.2 Changed

- Make Makefile clean targets modular
- Use img.shields.io for PyPi badges
- Get django-cas-server version in Makefile directly from setup.py (so now, the version is only written in one place)

3.24.3 Fixed

- Fix MySQLAuthUser when number of results != 1: In that case, call super anyway this the provided username.

3.25 v0.4.0 - 2015-12-15

commit: 7b4fac575449e50c2caff07f5798dba7f4e4857c

3.25.1 Added

- Add a help_text to pattern of ServicePattern
- Add a timeout to SLO requests
- Add logging capabilities (see README.rst for instruction)
- Add management commands that should be called on a regular basis to README.rst

3.26 v0.3.5 - 2015-12-12

commit: 51fa0861f550723171e52d58025fa789dccb8cde

3.26.1 Added

- Add badges to README.rst
- Document settings parameter in README.rst
- Add a “Features” section in README.rst

3.26.2 Changed

- Add a AuthUser auth class and use it as auth classes base class instead of DummyAuthUser

3.26.3 Fixed

- Fix minor errors and typos in README.rst

3.27 v0.3.4 - 2015-12-12

commit: 9fbfe19c550b147e8d0377108cdac8231cf0fb27

3.27.1 Added

- Add static files, templates and locales to the PyPi release by adding them to MANIFEST.in
- Add a Makefile with the build/install/clean/dist targets

3.28 v0.3.3 - 2015-12-12

commit: 16b700d0127abe33a1eabf5d5fe890aeb5167e5a

3.28.1 Added

- Add management commands and migrations to the package by adding there packages to setup.py packages list.

3.29 v0.3.2 - 2015-12-12 [YANKED]

commit: eef9490885bf665a53349573ddb9cbe844319b3e

3.29.1 Added

- Add migrations to setup.py package_data

3.30 v0.3.1 - 2015-12-12

commit: d0f6ed9ea3a4b3e2bf715fd218c460892c32e39f

3.30.1 Added

- Add a forgotten migration (remove auto_now_add=True from the User model)

3.31 v0.3.0 - 2015-12-12

commit: b69769d71a99806a69e300eca0d7c6744a2b327e

3.31.1 Added

- Django 1.9 compatibility (add tox and travis tests and fix some deprecated)

3.32 v0.2.1 - 2015-12-12

commit: 90e077dedb991d651822e9bb283470de8bddd7dd

First github and PyPi release

3.32.1 Fixed

- Prune .tox in MANIFEST.in
- add dist/ to .gitignore
- typo in setup.cfg

3.33 v0.2.0 - 2015-12-12 [YANKED]

commit: a071ad46d7cd76fc97eb86f2f538d330457c6767

3.34 v0.1.0 - 2015-05-22 [YANKED]

commit: 6981433bdf8a406992ba0c5e844a47d06ccc08fb

CHAPTER 4

Indices and tables

- `genindex`

C

- [cas_server](#), 60
- [cas_server.admin](#), 18
- [cas_server.apps](#), 20
- [cas_server.auth](#), 21
- [cas_server.cas](#), 24
- [cas_server.default_settings](#), 26
- [cas_server.federate](#), 30
- [cas_server.forms](#), 31
- [cas_server.models](#), 33
- [cas_server.templatetags](#), 18
- [cas_server.templatetags.cas_server](#), 17
- [cas_server.urls](#), 48
- [cas_server.utils](#), 48
- [cas_server.views](#), 52

A

abstract (*cas_server.models.JsonAttributes.Meta attribute*), 33
 abstract (*cas_server.models.Ticket.Meta attribute*), 43
 ajax (*cas_server.views.LoginView attribute*), 54
 ajax (*cas_server.views.LogoutView attribute*), 53
 allow_proxy_ticket (*cas_server.views.ValidateService attribute*), 58
 attribut (*cas_server.models.FilterAttributValue attribute*), 42
 attribut (*cas_server.models.ReplaceAttributValue attribute*), 42
 attributs (*cas_server.federate.CASFederateValidateUser attribute*), 30
 attributs (*cas_server.models.JsonAttributes attribute*), 33
 attributs (*cas_server.models.ServicePattern attribute*), 39
 attributs (*cas_server.models.User attribute*), 36
 attributs () (*cas_server.auth.AuthUser method*), 21
 attributs () (*cas_server.auth.CASFederateAuth method*), 24
 attributs () (*cas_server.auth.DBAuthUser method*), 22
 attributs () (*cas_server.auth.DjangoAuthUser method*), 23
 attributs () (*cas_server.auth.DummyAuthUser method*), 21
 attributs () (*cas_server.auth.LdapAuthUser method*), 23
 attributs () (*cas_server.auth.TestAuthUser method*), 21
 attributs_flat () (*cas_server.models.Ticket method*), 44
 Auth (*class in cas_server.views*), 57
 authenticated () (*cas_server.views.LoginView method*), 56
 AuthUser (*class in cas_server.auth*), 21

B

BadFilter, 38
 BadUsername, 38
 BaseInlines (*class in cas_server.admin*), 18
 BaseLogin (*class in cas_server.forms*), 31
 BootsrapForm (*class in cas_server.forms*), 31
 build_username () (*cas_server.models.FederatedIendityProvider method*), 34
 build_username_from_suffix () (*cas_server.models.FederatedIendityProvider static method*), 33

C

CAS_AUTH_CLASS (in *cas_server.default_settings*), 26 module
 CAS_AUTH_SHARED_SECRET (in *cas_server.default_settings*), 26 module
 CAS_COMPONENT_URLS (in *cas_server.default_settings*), 26 module
 CAS_ENABLE_AJAX_AUTH (in *cas_server.default_settings*), 28 module
 CAS_FAVICON_URL (in *cas_server.default_settings*), 26 module
 CAS_FEDERATE (in *cas_server.default_settings*), 28 module
 CAS_FEDERATE_REMEMBER_TIMEOUT (in *cas_server.default_settings*), 28 module
 CAS_INFO_MESSAGES (in *cas_server.default_settings*), 29 module
 CAS_INFO_MESSAGES_ORDER (in *cas_server.default_settings*), 29 module
 CAS_LDAP_ATTRS_VIEW (in *cas_server.default_settings*), 28 module
 CAS_LDAP_BASE_DN (in *cas_server.default_settings*), 28 module
 CAS_LDAP_PASSWORD (in *cas_server.default_settings*), 28 module
 CAS_LDAP_PASSWORD_ATTR (in *cas_server.default_settings*), 28 module

CAS_LDAP_PASSWORD_CHARSET	(in module <i>cas_server.default_settings</i>), 28	CAS_REMOVE_DJANGO_SESSION_COOKIE_ON_LOGOUT	(in module <i>cas_server.default_settings</i>), 29
CAS_LDAP_PASSWORD_CHECK	(in module <i>cas_server.default_settings</i>), 28	cas_server (module), 60	
CAS_LDAP_SERVER	(in module <i>cas_server.default_settings</i>), 28	cas_server.admin (module), 18	
CAS_LDAP_USER	(in module <i>cas_server.default_settings</i>), 28	cas_server.apps (module), 20	
CAS_LDAP_USER_QUERY	(in module <i>cas_server.default_settings</i>), 28	cas_server.auth (module), 21	
CAS_LDAP_USERNAME_ATTR	(in module <i>cas_server.default_settings</i>), 28	cas_server.cas (module), 24	
CAS_LOGGED_TEMPLATE	(in module <i>cas_server.default_settings</i>), 26	cas_server.default_settings (module), 26	
CAS_LOGIN_TEMPLATE	(in module <i>cas_server.default_settings</i>), 26	cas_server.federate (module), 30	
CAS_LOGIN_TICKET_PREFIX	(in module <i>cas_server.default_settings</i>), 27	cas_server.forms (module), 31	
CAS_LOGO_URL	(in module <i>cas_server.default_settings</i>), 26	cas_server.models (module), 33	
CAS_LOGOUT_TEMPLATE	(in module <i>cas_server.default_settings</i>), 26	cas_server.templatetags (module), 18	
CAS_LT_LEN (in module <i>cas_server.default_settings</i>), 27		cas_server.templatetags.cas_server (module), 17	
CAS_NEW_VERSION_EMAIL_WARNING (in module <i>cas_server.default_settings</i>), 28		cas_server.urls (module), 48	
CAS_NEW_VERSION_HTML_WARNING (in module <i>cas_server.default_settings</i>), 28		cas_server.utils (module), 48	
CAS_NEW_VERSION_JSON_URL (in module <i>cas_server.default_settings</i>), 29		cas_server.views (module), 52	
CAS_PGT_LEN (in module <i>cas_server.default_settings</i>), 27		CAS_SERVICE_TICKET_PREFIX (in module <i>cas_server.default_settings</i>), 27	
CAS_PGT_VALIDITY (in module <i>cas_server.default_settings</i>), 26		CAS_SHOW_POWERED (in module <i>cas_server.default_settings</i>), 26	
CAS_PGTIOW_LEN (in module <i>cas_server.default_settings</i>), 27		CAS_SHOW_SERVICE_MESSAGES (in module <i>cas_server.default_settings</i>), 29	
cas_protocol_version (in module <i>cas_server.models.FederatedIdentityProvider</i> attribute), 33		CAS_SLO_MAX_PARALLEL_REQUESTS (in module <i>cas_server.default_settings</i>), 26	
CAS_PROXY_CA_CERTIFICATE_PATH (in module <i>cas_server.default_settings</i>), 26		CAS_SLO_TIMEOUT (in module <i>cas_server.default_settings</i>), 26	
CAS_PROXY_GRANTING_TICKET_IOW_PREFIX (in module <i>cas_server.default_settings</i>), 27		CAS_SQL_DBCHARSET (in module <i>cas_server.default_settings</i>), 27	
CAS_PROXY_GRANTING_TICKET_PREFIX (in module <i>cas_server.default_settings</i>), 27		CAS_SQL_DBNAME (in module <i>cas_server.default_settings</i>), 27	
CAS_PROXY_TICKET_PREFIX (in module <i>cas_server.default_settings</i>), 27		CAS_SQL_HOST (in module <i>cas_server.default_settings</i>), 27	
CAS_PT_LEN (in module <i>cas_server.default_settings</i>), 27		CAS_SQL_PASSWORD (in module <i>cas_server.default_settings</i>), 27	
CAS_REDIRECT_TO_LOGIN_AFTER_LOGOUT (in module <i>cas_server.default_settings</i>), 26		CAS_SQL_PASSWORD_CHARSET (in module <i>cas_server.default_settings</i>), 27	
CAS_REMOVE_DJANGO_CSRF_COOKIE_ON_LOGOUT (in module <i>cas_server.default_settings</i>), 29		CAS_SQL_PASSWORD_CHECK (in module <i>cas_server.default_settings</i>), 27	
CAS_REMOVE_DJANGO_LANGUAGE_COOKIE_ON_LOGOUT		CAS_SQL_USER_QUERY (in module <i>cas_server.default_settings</i>), 27	
		CAS_SQL_USERNAME (in module <i>cas_server.default_settings</i>), 27	
		CAS_ST_LEN (in module <i>cas_server.default_settings</i>), 27	
		CAS_TEST_ATTRIBUTES (in module <i>cas_server.default_settings</i>), 28	
		CAS_TEST_PASSWORD (in module <i>cas_server.default_settings</i>), 28	
		CAS_TEST_USER (in module <i>cas_server.default_settings</i>), 28	
		CAS_TGT_VALIDITY (in module <i>cas_server.default_settings</i>), 26	

CAS_TICKET_LEN (in module `cas_server.default_settings`), 27
 CAS_TICKET_TIMEOUT (in module `cas_server.default_settings`), 27
 CAS_TICKET_VALIDITY (in module `cas_server.default_settings`), 26
 CAS_WARN_TEMPLATE (in module `cas_server.default_settings`), 26
 CasAppConfig (class in `cas_server.apps`), 20
 CASClient (class in `cas_server.cas`), 24
 CASClientBase (class in `cas_server.cas`), 24
 CASClientV1 (class in `cas_server.cas`), 24
 CASClientV2 (class in `cas_server.cas`), 25
 CASClientV3 (class in `cas_server.cas`), 25
 CASClientWithSAMLV1 (class in `cas_server.cas`), 25
 CASError, 24
 CASFederateAuth (class in `cas_server.auth`), 23
 CASFederateValidateUser (class in `cas_server.federate`), 30
 check_lt() (`cas_server.views.LoginView` method), 55
 check_password() (in module `cas_server.utils`), 52
 check_user() (`cas_server.models.ServicePattern` method), 39
 clean() (`cas_server.forms.FederateUserCredential` method), 32
 clean() (`cas_server.forms.UserCredential` method), 32
 clean_deleted_sessions() (`cas_server.models.FederateSLO` class method), 35
 clean_deleted_sessions() (`cas_server.models.User` class method), 36
 clean_old_entries() (`cas_server.models.FederatedUser` class method), 34
 clean_old_entries() (`cas_server.models.Ticket` class method), 43
 clean_old_entries() (`cas_server.models.User` class method), 36
 clean_old_entries() (`cas_server.models.UserAttributes` class method), 35
 clean_sessions() (`cas_server.federate.CASFederateValidateUser` method), 31
 clear_expired() (`cas_server.default_settings.SessionStore` class method), 30
 client (`cas_server.federate.CASFederateValidateUser` attribute), 30
 code (`cas_server.views.ValidationBaseError` attribute), 57
 common() (`cas_server.views.LoginView` method), 57
 context() (`cas_server.views.SamlValidateError` method), 59
 context() (in module `cas_server.utils`), 48
 copy_params() (in module `cas_server.utils`), 49
 create() (`cas_server.default_settings.SessionStore` method), 29
 create_model_instance() (`cas_server.default_settings.SessionStore` method), 29
 creation (`cas_server.models.Ticket` attribute), 43
 crypt_salt_is_valid() (in module `cas_server.utils`), 50
 CsrfExemptView (class in `cas_server.views`), 53

D

 date (`cas_server.models.User` attribute), 36
 DBAuthUser (class in `cas_server.auth`), 22
 decode_version() (in module `cas_server.utils`), 52
 delete() (`cas_server.default_settings.SessionStore` method), 29
 delete() (`cas_server.models.User` method), 36
 delete_cookies() (`cas_server.views.LogoutView` static method), 53
 dictfetchall() (in module `cas_server.utils`), 52
 dispatch() (`cas_server.views.CsrfExemptView` method), 53
 display (`cas_server.models.FederatedIdentityProvider` attribute), 33
 DjangoAuthUser (class in `cas_server.auth`), 23
 DummyAuthUser (class in `cas_server.auth`), 21

E

 exists() (`cas_server.default_settings.SessionStore` method), 29
 extra (`cas_server.admin.BaseInlines` attribute), 18

F

 FederateAuth (class in `cas_server.views`), 53
 federated_username (`cas_server.federate.CASFederateValidateUser` attribute), 30
 federated_username (`cas_server.models.FederatedUser` attribute), 34
 FederatedIdentityProvider (class in `cas_server.models`), 33
 FederatedIdentityProvider.DoesNotExist, 34
 FederatedIdentityProvider.MultipleObjectsReturned, 34
 FederatedIdentityProviderAdmin (class in `cas_server.admin`), 20
 FederatedUser (class in `cas_server.models`), 34
 FederatedUser.DoesNotExist, 34

FederatedUser.MultipleObjectsReturned, 35

federateduser_set (*cas_server.models.FederatedIdentityProvider attribute*), 34

FederatedUserAdmin (*class in cas_server.admin*), 20

FederateSelect (*class in cas_server.forms*), 31

FederateSLO (*class in cas_server.models*), 35

FederateSLO.DoesNotExist, 35

FederateSLO.MultipleObjectsReturned, 35

FederateUserCredential (*class in cas_server.forms*), 32

fetch_saml_validation() (*cas_server.cas.CASClientWithSAMLV1 method*), 25

fields (*cas_server.admin.FederatedIdentityProviderAdmin attribute*), 20

fields (*cas_server.admin.FederatedUserAdmin attribute*), 20

fields (*cas_server.admin.UserAdmin attribute*), 19

fields (*cas_server.admin.UserAdminInlines attribute*), 18

fields (*cas_server.admin.UserAttributesAdmin attribute*), 20

FilterAttributeValue (*class in cas_server.models*), 41

FilterAttributeValue.DoesNotExist, 42

FilterAttributeValue.MultipleObjectsReturned, 42

FilterAttributeValueInline (*class in cas_server.admin*), 19

filters (*cas_server.models.ServicePattern attribute*), 39

form (*cas_server.admin.UserAdminInlines attribute*), 18

form (*cas_server.views.LoginView attribute*), 54

G

gateway (*cas_server.forms.BaseLogin attribute*), 31

gateway (*cas_server.views.LoginView attribute*), 54

gen_lt() (*cas_server.views.LoginView method*), 55

gen_lt() (*in module cas_server.utils*), 50

gen_pgt() (*in module cas_server.utils*), 50

gen_pgtiou() (*in module cas_server.utils*), 50

gen_pt() (*in module cas_server.utils*), 50

gen_saml_id() (*in module cas_server.utils*), 50

gen_st() (*in module cas_server.utils*), 50

get() (*cas_server.models.Ticket class method*), 44

get() (*cas_server.views.FederateAuth method*), 54

get() (*cas_server.views.LoginView method*), 56

get() (*cas_server.views.LogoutView method*), 53

get() (*cas_server.views.Proxy method*), 59

get() (*cas_server.views.Validate static method*), 57

get() (*cas_server.views.ValidateService method*), 58

get_cas_client() (*cas_server.views.FederateAuth method*), 53

get_cas_protocol_version_display() (*cas_server.models.FederatedIdentityProvider method*), 34

get_class() (*cas_server.models.Ticket static method*), 43

get_conn() (*cas_server.auth.LdapAuthUser class method*), 23

get_current_url() (*in module cas_server.utils*), 49

get_from_federated_username() (*cas_server.models.FederatedUser class method*), 34

get_login_url() (*cas_server.cas.CASClientBase method*), 24

get_login_url() (*cas_server.federate.CASFederateValidateUser method*), 30

get_logout_url() (*cas_server.cas.CASClientBase method*), 24

get_logout_url() (*cas_server.federate.CASFederateValidateUser method*), 30

get_model_class() (*cas_server.default_settings.SessionStore class method*), 29

get_next_by_creation() (*cas_server.models.ProxyGrantingTicket method*), 46

get_next_by_creation() (*cas_server.models.ProxyTicket method*), 45

get_next_by_creation() (*cas_server.models.ServiceTicket method*), 44

get_next_by_creation() (*cas_server.models.Ticket method*), 44

get_next_by_date() (*cas_server.models.User method*), 37

get_next_by_last_login() (*cas_server.models.User method*), 37

get_next_by_last_update() (*cas_server.models.FederatedUser method*), 35

get_page_charset() (*cas_server.cas.CASClientBase static method*), 24

get_previous_by_creation() (*cas_server.models.ProxyGrantingTicket method*), 46

get_previous_by_creation() (*cas_server.models.ProxyTicket method*), 45

get_previous_by_creation() (*cas_server.models.ServiceTicket method*), 44

get_previous_by_creation()

(*cas_server.models.Ticket* method), 44
get_previous_by_date()
 (*cas_server.models.User* method), 37
get_previous_by_last_login()
 (*cas_server.models.User* method), 37
get_previous_by_last_update()
 (*cas_server.models.FederatedUser* method), 35
get_proxy_ticket()
 (*cas_server.cas.CASClientBase* method), 24
get_proxy_url() (*cas_server.cas.CASClientBase* method), 24
get_salt() (*cas_server.utils.LdapHashUserPassword* class method), 51
get_saml_assertion()
 (*cas_server.cas.CASClientWithSAMLv1* class method), 25
get_saml_slos() (*cas_server.cas.SingleLogoutMixin* class method), 24
get_scheme() (*cas_server.utils.LdapHashUserPassword* class method), 51
get_service_url() (*cas_server.models.User* method), 36
get_ticket() (*cas_server.models.User* method), 36
get_tuple() (in module *cas_server.utils*), 50
get_verification_response()
 (*cas_server.cas.CASClientV2* method), 25

H

hash() (*cas_server.utils.LdapHashUserPassword* class method), 51

I

id (*cas_server.models.FederatedIdentityProvider* attribute), 34
id (*cas_server.models.FederatedUser* attribute), 35
id (*cas_server.models.FederateSLO* attribute), 35
id (*cas_server.models.FilterAttributeValue* attribute), 42
id (*cas_server.models.NewVersionWarning* attribute), 47
id (*cas_server.models.Proxy* attribute), 47
id (*cas_server.models.ProxyGrantingTicket* attribute), 46
id (*cas_server.models.ProxyTicket* attribute), 45
id (*cas_server.models.ReplaceAttributeName* attribute), 41
id (*cas_server.models.ReplaceAttributeValue* attribute), 42
id (*cas_server.models.ServicePattern* attribute), 40
id (*cas_server.models.ServiceTicket* attribute), 44
id (*cas_server.models.User* attribute), 37
id (*cas_server.models.UserAttributes* attribute), 35
id (*cas_server.models.Username* attribute), 41
import_attr() (in module *cas_server.utils*), 48

init_form() (*cas_server.views.LoginView* method), 56
init_get() (*cas_server.views.LoginView* method), 55
init_get() (*cas_server.views.LogoutView* method), 53
init_post() (*cas_server.views.LoginView* method), 55
inlines (*cas_server.admin.ServicePatternAdmin* attribute), 19
inlines (*cas_server.admin.UserAdmin* attribute), 19
INVALID_LOGIN_TICKET
 (*cas_server.views.LoginView* attribute), 55
is_checkbox() (in module *cas_server.template_tags.cas_server*), 17
is_hidden() (in module *cas_server.template_tags.cas_server*), 17

J

json_encode() (in module *cas_server.utils*), 48
json_response() (in module *cas_server.utils*), 48
JsonAttributes (class in *cas_server.models*), 33
JsonAttributes.Meta (class in *cas_server.models*), 33

L

last_login (*cas_server.models.User* attribute), 36
last_update (*cas_server.models.FederatedUser* attribute), 34
last_version() (in module *cas_server.utils*), 52
LdapAuthUser (class in *cas_server.auth*), 22
LdapHashUserPassword (class in *cas_server.utils*), 51
LdapHashUserPassword.BadHash, 51
LdapHashUserPassword.BadSalt, 51
LdapHashUserPassword.BadScheme, 51
list_display (*cas_server.admin.FederatedIdentityProviderAdmin* attribute), 20
list_display (*cas_server.admin.FederatedUserAdmin* attribute), 20
list_display (*cas_server.admin.ServicePatternAdmin* attribute), 20
list_display (*cas_server.admin.UserAdmin* attribute), 19
load() (*cas_server.default_settings.SessionStore* method), 29
logger (in module *cas_server.federate*), 30
logger (in module *cas_server.models*), 33
logger (in module *cas_server.utils*), 48
LoginView (class in *cas_server.views*), 54
logout() (*cas_server.models.Ticket* method), 43
logout() (*cas_server.models.User* method), 36
logout() (*cas_server.views.LogoutMixin* method), 53
logout_redirect_param_name
 (*cas_server.cas.CASClientBase* attribute),

24
[logout_redirect_param_name](#)
 ([cas_server.cas.CASClientV1](#) attribute),
 25
[logout_redirect_param_name](#)
 ([cas_server.cas.CASClientV2](#) attribute),
 25
[logout_redirect_param_name](#)
 ([cas_server.cas.CASClientV3](#) attribute),
 25
[logout_request\(\)](#) (in module [cas_server.utils](#)), 52
[LogoutMixin](#) (class in [cas_server.views](#)), 52
[LogoutView](#) (class in [cas_server.views](#)), 53
[lt](#) ([cas_server.forms.BaseLogin](#) attribute), 31

M

[media](#) ([cas_server.admin.BaseInlines](#) attribute), 18
[media](#) ([cas_server.admin.FederatedIendityProviderAdmin](#) attribute), 20
[media](#) ([cas_server.admin.FederatedUserAdmin](#) attribute), 20
[media](#) ([cas_server.admin.FilterAttributValueInline](#) attribute), 19
[media](#) ([cas_server.admin.ProxyGrantingInline](#) attribute), 18
[media](#) ([cas_server.admin.ProxyTicketInline](#) attribute), 18
[media](#) ([cas_server.admin.ReplaceAttributNameInline](#) attribute), 19
[media](#) ([cas_server.admin.ReplaceAttributValueInline](#) attribute), 19
[media](#) ([cas_server.admin.ServicePatternAdmin](#) attribute), 20
[media](#) ([cas_server.admin.ServiceTicketInline](#) attribute), 18
[media](#) ([cas_server.admin.UserAdmin](#) attribute), 19
[media](#) ([cas_server.admin.UserAdminInlines](#) attribute), 18
[media](#) ([cas_server.admin.UserAttributesAdmin](#) attribute), 20
[media](#) ([cas_server.admin.UsernamesInline](#) attribute), 19
[method](#) ([cas_server.views.LoginView](#) attribute), 54
[model](#) ([cas_server.admin.FilterAttributValueInline](#) attribute), 19
[model](#) ([cas_server.admin.ProxyGrantingInline](#) attribute), 18
[model](#) ([cas_server.admin.ProxyTicketInline](#) attribute), 18
[model](#) ([cas_server.admin.ReplaceAttributNameInline](#) attribute), 19
[model](#) ([cas_server.admin.ReplaceAttributValueInline](#) attribute), 19
[model](#) ([cas_server.admin.ServiceTicketInline](#) attribute), 18

[model](#) ([cas_server.admin.UsernamesInline](#) attribute), 19
[model](#) ([cas_server.default_settings.SessionStore](#) attribute), 29
[msg](#) ([cas_server.views.ValidationBaseError](#) attribute), 57
[MysqlAuthUser](#) (class in [cas_server.auth](#)), 22

N

[name](#) ([cas_server.apps.CasAppConfig](#) attribute), 20
[name](#) ([cas_server.models.ReplaceAttributName](#) attribute), 41
[name](#) ([cas_server.models.ServicePattern](#) attribute), 38
[NewVersionWarning](#) (class in [cas_server.models](#)), 47
[NewVersionWarning.DoesNotExist](#), 47
[NewVersionWarning.MultipleObjectsReturned](#), 47
[not_authenticated\(\)](#)
 ([cas_server.views.LoginView](#) method), 56

O

[objects](#) ([cas_server.models.FederatedIendityProvider](#) attribute), 34
[objects](#) ([cas_server.models.FederatedUser](#) attribute), 35
[objects](#) ([cas_server.models.FederateSLO](#) attribute), 35
[objects](#) ([cas_server.models.FilterAttributValue](#) attribute), 42
[objects](#) ([cas_server.models.NewVersionWarning](#) attribute), 47
[objects](#) ([cas_server.models.Proxy](#) attribute), 47
[objects](#) ([cas_server.models.ProxyGrantingTicket](#) attribute), 46
[objects](#) ([cas_server.models.ProxyTicket](#) attribute), 45
[objects](#) ([cas_server.models.ReplaceAttributName](#) attribute), 41
[objects](#) ([cas_server.models.ReplaceAttributValue](#) attribute), 42
[objects](#) ([cas_server.models.ServicePattern](#) attribute), 40
[objects](#) ([cas_server.models.ServiceTicket](#) attribute), 45
[objects](#) ([cas_server.models.User](#) attribute), 37
[objects](#) ([cas_server.models.UserAttributes](#) attribute), 35
[objects](#) ([cas_server.models.Username](#) attribute), 41

P

[parse_attributes_xml_element\(\)](#)
 ([cas_server.cas.CASClientV2](#) class method), 25
[parse_attributes_xml_element\(\)](#)
 ([cas_server.cas.CASClientV3](#) class method), 25
[parse_response_xml\(\)](#)
 ([cas_server.cas.CASClientV2](#) class method), 25
[password](#) ([cas_server.forms.UserCredential](#) attribute), 32

[pattern \(cas_server.models.FilterAttributValue attribute\), 42](#)
[pattern \(cas_server.models.ReplaceAttributValue attribute\), 42](#)
[pattern \(cas_server.models.ServicePattern attribute\), 38](#)
[pgt \(cas_server.views.Proxy attribute\), 59](#)
[pgt_url \(cas_server.views.ValidateService attribute\), 58](#)
[pos \(cas_server.models.FederatedIendityProvider attribute\), 33](#)
[pos \(cas_server.models.ServicePattern attribute\), 38](#)
[post \(\) \(cas_server.views.Auth static method\), 57](#)
[post \(\) \(cas_server.views.FederateAuth method\), 54](#)
[post \(\) \(cas_server.views.LoginView method\), 55](#)
[post \(\) \(cas_server.views.SamlValidate method\), 59](#)
[PREFIX \(cas_server.models.ProxyGrantingTicket attribute\), 46](#)
[PREFIX \(cas_server.models.ProxyTicket attribute\), 45](#)
[PREFIX \(cas_server.models.ServiceTicket attribute\), 44](#)
[process_get \(\) \(cas_server.views.LoginView method\), 56](#)
[process_pgturl \(\) \(cas_server.views.ValidateService method\), 58](#)
[process_post \(\) \(cas_server.views.LoginView method\), 55](#)
[process_proxy \(\) \(cas_server.views.Proxy method\), 59](#)
[process_ticket \(\) \(cas_server.views.SamlValidate method\), 60](#)
[process_ticket \(\) \(cas_server.views.ValidateService method\), 58](#)
[provider \(cas_server.federate.CASFederateValidateUser attribute\), 30](#)
[provider \(cas_server.forms.FederateSelect attribute\), 31](#)
[provider \(cas_server.models.FederatedUser attribute\), 34](#)
[provider_id \(cas_server.models.FederatedUser attribute\), 35](#)
[proxies \(cas_server.models.ProxyTicket attribute\), 45](#)
[proxy \(cas_server.models.ServicePattern attribute\), 38](#)
[Proxy \(class in cas_server.models\), 47](#)
[Proxy \(class in cas_server.views\), 59](#)
[Proxy.DoesNotExist, 47](#)
[Proxy.MultipleObjectsReturned, 47](#)
[proxy_callback \(cas_server.models.ServicePattern attribute\), 38](#)
[proxy_ticket \(cas_server.models.Proxy attribute\), 47](#)
[proxy_ticket_id \(cas_server.models.Proxy attribute\), 47](#)
[ProxyGrantingInline \(class in cas_server.admin\), 18](#)
[proxygrantingticket \(cas_server.models.ServicePattern attribute\), 40](#)
[proxygrantingticket \(cas_server.models.User attribute\), 37](#)
[ProxyGrantingTicket \(class in cas_server.models\), 46](#)
[ProxyGrantingTicket.DoesNotExist, 46](#)
[ProxyGrantingTicket.MultipleObjectsReturned, 46](#)
[proxyticket \(cas_server.models.ServicePattern attribute\), 40](#)
[proxyticket \(cas_server.models.User attribute\), 37](#)
[ProxyTicket \(class in cas_server.models\), 45](#)
[ProxyTicket.DoesNotExist, 45](#)
[ProxyTicket.MultipleObjectsReturned, 45](#)
[ProxyTicketInline \(class in cas_server.admin\), 18](#)
[python_2_unicode_compatible \(\) \(in module cas_server.models\), 33](#)
[python_2_unicode_compatible \(\) \(in module cas_server.views\), 52](#)

R

[re_path \(\) \(in module cas_server.urls\), 48](#)
[readonly_fields \(cas_server.admin.UserAdmin attribute\), 19](#)
[readonly_fields \(cas_server.admin.UserAdminInlines attribute\), 18](#)
[redirect_params \(\) \(in module cas_server.utils\), 48](#)
[regex_validator \(\) \(in module cas_server.utils\), 52](#)
[register_slo \(\) \(cas_server.federate.CASFederateValidateUser static method\), 31](#)
[remember \(cas_server.forms.FederateSelect attribute\), 32](#)
[render \(\) \(cas_server.views.ValidationBaseError method\), 57](#)
[renew \(cas_server.forms.BaseLogin attribute\), 31](#)
[renew \(cas_server.models.Ticket attribute\), 43](#)
[renew \(cas_server.views.LoginView attribute\), 54](#)
[renew \(cas_server.views.ValidateService attribute\), 58](#)
[renewed \(cas_server.views.LoginView attribute\), 54](#)
[replace \(cas_server.models.ReplaceAttributName attribute\), 41](#)
[replace \(cas_server.models.ReplaceAttributValue attribute\), 42](#)
[ReplaceAttributName \(class in cas_server.models\), 41](#)
[ReplaceAttributName.DoesNotExist, 41](#)
[ReplaceAttributName.MultipleObjectsReturned, 41](#)
[ReplaceAttributNameInline \(class in cas_server.admin\), 19](#)

[ReplaceAttributeValue \(class in cas_server.models\), 42](#)
[ReplaceAttributeValue.DoesNotExist, 42](#)
[ReplaceAttributeValue.MultipleObjectsReturned, 42](#)
[ReplaceAttributeValueInline \(class in cas_server.admin\), 19](#)
[replacements \(cas_server.models.ServicePattern attribute\), 40](#)
[request \(cas_server.views.LoginView attribute\), 54](#)
[request \(cas_server.views.LogoutView attribute\), 53](#)
[request \(cas_server.views.Proxy attribute\), 59](#)
[request \(cas_server.views.SamlValidate attribute\), 59](#)
[request \(cas_server.views.ValidateService attribute\), 58](#)
[restrict_users \(cas_server.models.ServicePattern attribute\), 38](#)
[ReturnUnicode \(class in cas_server.cas\), 24](#)
[reverse_params \(\) \(in module cas_server.utils\), 48](#)
[root \(cas_server.views.SamlValidate attribute\), 59](#)

S

[SamlValidate \(class in cas_server.views\), 59](#)
[SamlValidateError, 59](#)
[save \(\) \(cas_server.default_settings.SessionStore method\), 29](#)
[schemes_nosalt \(cas_server.utils.LdapHashUserPassword attribute\), 51](#)
[schemes_salt \(cas_server.utils.LdapHashUserPassword attribute\), 51](#)
[send_mails \(\) \(cas_server.models.NewVersionWarning class method\), 47](#)
[send_slos \(\) \(cas_server.models.Ticket static method\), 43](#)
[server_url \(cas_server.models.FederatedIdentityProvider attribute\), 33](#)
[service \(cas_server.forms.BaseLogin attribute\), 31](#)
[service \(cas_server.models.Ticket attribute\), 43](#)
[service \(cas_server.views.LoginView attribute\), 54](#)
[service \(cas_server.views.LogoutView attribute\), 53](#)
[service \(cas_server.views.ValidateService attribute\), 58](#)
[service_login \(\) \(cas_server.views.LoginView method\), 56](#)
[service_pattern \(cas_server.models.FilterAttributeValue attribute\), 42](#)
[service_pattern \(cas_server.models.ProxyGrantingTicket attribute\), 46](#)
[service_pattern \(cas_server.models.ProxyTicket attribute\), 46](#)
[service_pattern \(cas_server.models.ReplaceAttributeName attribute\), 41](#)
[service_pattern \(cas_server.models.ReplaceAttributeValue attribute\), 42](#)
[service_pattern \(cas_server.models.ServiceTicket attribute\), 45](#)
[service_pattern \(cas_server.models.Ticket attribute\), 43](#)
[service_pattern \(cas_server.models.Username attribute\), 41](#)
[service_pattern_id \(cas_server.models.FilterAttributeValue attribute\), 42](#)
[service_pattern_id \(cas_server.models.ReplaceAttributeName attribute\), 41](#)
[service_pattern_id \(cas_server.models.ReplaceAttributeValue attribute\), 42](#)
[service_pattern_id \(cas_server.models.Ticket attribute\), 44](#)
[service_pattern_id \(cas_server.models.Username attribute\), 41](#)
[service_url \(cas_server.views.FederateAuth attribute\), 53](#)
[ServicePattern \(class in cas_server.models\), 38](#)
[ServicePattern.DoesNotExist, 39](#)
[ServicePattern.MultipleObjectsReturned, 39](#)
[ServicePatternAdmin \(class in cas_server.admin\), 19](#)
[ServicePatternException, 38](#)
[serviceticket \(cas_server.models.ServicePattern attribute\), 40](#)
[serviceticket \(cas_server.models.User attribute\), 37](#)
[ServiceTicket \(class in cas_server.models\), 44](#)
[ServiceTicket.DoesNotExist, 44](#)
[ServiceTicket.MultipleObjectsReturned, 44](#)
[ServiceTicketInline \(class in cas_server.admin\), 18](#)
[session_key \(cas_server.models.FederateSLO attribute\), 35](#)
[session_key \(cas_server.models.User attribute\), 36](#)
[SessionStore \(class in cas_server.default_settings\), 29](#)
[set_cookie \(\) \(in module cas_server.utils\), 49](#)
[single_log_out \(cas_server.models.ServicePattern attribute\), 38](#)
[single_log_out \(cas_server.models.Ticket attribute\), 43](#)
[single_log_out_callback \(cas_server.models.ServicePattern attribute\), 39](#)
[SingleLogoutMixin \(class in cas_server.cas\), 24](#)
[SamlAuthUser \(class in cas_server.auth\), 22](#)
[suffix \(cas_server.models.FederatedIdentityProvider](#)

attribute), 33

T

target (*cas_server.views.SamlValidate attribute*), 59
target_service (*cas_server.views.Proxy attribute*), 59
template (*cas_server.views.SamlValidateError attribute*), 59
template (*cas_server.views.ValidateError attribute*), 58
test_password() (*cas_server.auth.AuthUser method*), 21
test_password() (*cas_server.auth.CASFederateAuth method*), 23
test_password() (*cas_server.auth.DjangoAuthUser method*), 23
test_password() (*cas_server.auth.DummyAuthUser method*), 21
test_password() (*cas_server.auth.LdapAuthUser method*), 23
test_password() (*cas_server.auth.MysqlAuthUser method*), 22
test_password() (*cas_server.auth.SqlAuthUser method*), 22
test_password() (*cas_server.auth.TestAuthUser method*), 21
TestAuthUser (*class in cas_server.auth*), 21
ticket (*cas_server.models.FederatedUser attribute*), 34
ticket (*cas_server.models.FederateSLO attribute*), 35
ticket (*cas_server.views.LoginView attribute*), 55
ticket (*cas_server.views.SamlValidate attribute*), 59
ticket (*cas_server.views.ValidateService attribute*), 58
Ticket (*class in cas_server.models*), 42
Ticket.DoesNotExist, 43
Ticket.Meta (*class in cas_server.models*), 42
TicketForm (*class in cas_server.forms*), 32
TIMEOUT (*cas_server.models.Ticket attribute*), 43

U

u() (*cas_server.cas.ReturnUnicode static method*), 24
unpack_nested_exception() (*in module cas_server.utils*), 49
update_url() (*in module cas_server.utils*), 49
url (*cas_server.models.Proxy attribute*), 47
url (*cas_server.views.LogoutView attribute*), 53
url_suffix (*cas_server.cas.CASClientV2 attribute*), 25
url_suffix (*cas_server.cas.CASClientV3 attribute*), 25
user (*cas_server.auth.CASFederateAuth attribute*), 23
user (*cas_server.auth.DBAuthUser attribute*), 22
user (*cas_server.auth.DjangoAuthUser attribute*), 23

user (*cas_server.models.ProxyGrantingTicket attribute*), 47
user (*cas_server.models.ProxyTicket attribute*), 46
user (*cas_server.models.ServiceTicket attribute*), 45
user (*cas_server.models.Ticket attribute*), 43
user (*cas_server.views.LoginView attribute*), 54
User (*class in cas_server.models*), 35
User.DoesNotExist, 37
User.MultipleObjectsReturned, 37
USER_ALREADY_LOGGED (*cas_server.views.LoginView attribute*), 55
USER_AUTHENTICATED (*cas_server.views.LoginView attribute*), 55
user_field (*cas_server.models.ServicePattern attribute*), 38
user_id (*cas_server.models.Ticket attribute*), 44
USER_LOGIN_FAILURE (*cas_server.views.LoginView attribute*), 55
USER_LOGIN_OK (*cas_server.views.LoginView attribute*), 55
USER_NOT_AUTHENTICATED (*cas_server.views.LoginView attribute*), 55
UserAdmin (*class in cas_server.admin*), 18
UserAdminInlines (*class in cas_server.admin*), 18
UserAttributes (*class in cas_server.models*), 35
UserAttributes.DoesNotExist, 35
UserAttributes.MultipleObjectsReturned, 35
UserAttributesAdmin (*class in cas_server.admin*), 20
UserCredential (*class in cas_server.forms*), 32
UserFieldNotDefined, 38
username (*cas_server.auth.AuthUser attribute*), 21
username (*cas_server.federate.CASFederateValidateUser attribute*), 30
username (*cas_server.forms.UserCredential attribute*), 32
username (*cas_server.models.FederatedUser attribute*), 34
username (*cas_server.models.FederateSLO attribute*), 35
username (*cas_server.models.User attribute*), 36
username (*cas_server.models.UserAttributes attribute*), 35
username (*cas_server.views.LoginView attribute*), 55
Username (*class in cas_server.models*), 41
username() (*cas_server.models.Ticket method*), 43
Username.DoesNotExist, 41
Username.MultipleObjectsReturned, 41
usernames (*cas_server.models.ServicePattern attribute*), 40
UsernamesInline (*class in cas_server.admin*), 19

V

[validate \(cas_server.models.Ticket attribute\), 43](#)
[Validate \(class in cas_server.views\), 57](#)
[validate\(\) \(cas_server.models.ServicePattern class method\), 39](#)
[ValidateError, 58](#)
[ValidateService \(class in cas_server.views\), 58](#)
[ValidationBaseError, 57](#)
[VALIDITY \(cas_server.models.ProxyGrantingTicket attribute\), 46](#)
[VALIDITY \(cas_server.models.Ticket attribute\), 43](#)
[value \(cas_server.models.ProxyGrantingTicket attribute\), 46](#)
[value \(cas_server.models.ProxyTicket attribute\), 45](#)
[value \(cas_server.models.ServiceTicket attribute\), 44](#)
[value \(cas_server.models.Username attribute\), 41](#)
[verbose_name \(cas_server.apps.CasAppConfig attribute\), 20](#)
[verbose_name \(cas_server.models.FederatedIdentityProvider attribute\), 33](#)
[verify_response\(\) \(cas_server.cas.CASClientV2 class method\), 25](#)
[verify_response\(\) \(cas_server.cas.CASClientV3 class method\), 25](#)
[verify_ticket\(\) \(cas_server.cas.CASClientBase method\), 24](#)
[verify_ticket\(\) \(cas_server.cas.CASClientV1 method\), 25](#)
[verify_ticket\(\) \(cas_server.cas.CASClientV2 method\), 25](#)
[verify_ticket\(\) \(cas_server.cas.CASClientWithSAMLVI method\), 25](#)
[verify_ticket\(\) \(cas_server.federate.CASFederateValidateUser method\), 30](#)
[version \(cas_server.models.NewVersionWarning attribute\), 47](#)
[VERSION \(in module cas_server\), 60](#)

W

[warn \(cas_server.forms.FederateSelect attribute\), 32](#)
[warn \(cas_server.forms.UserCredential attribute\), 32](#)
[warn \(cas_server.views.LoginView attribute\), 54](#)
[warned \(cas_server.forms.WarnForm attribute\), 31](#)
[warned \(cas_server.views.LoginView attribute\), 55](#)
[WarnForm \(class in cas_server.forms\), 31](#)